Service Manual

PIONEER®
The Art of Entertainment



ORDER NO.
RRV1947

DIGITAL VIDEO DISC PLAYER

DVD-V7200

THIS MANUAL IS APPLICABLE TO THE FOLLOWING MODEL(S) AND TYPE(S).

Type	Model	Power Requirement	Remarks
	DVD-V7200		
KU/CA	◯	AC120V	

- **Refer to the service guide RRV1896 for DV-505. IC information is described in the service guide.**

CONTENTS

PIONEER ELECTRONIC CORPORATION 4-1, Meguro 1-Chome, Meguro-ku, Tokyo 153-8654, Japan
PIONEER ELECTRONICS SERVICE, INC. P.O. Box 1760, Long Beach, CA 90801-1760, U.S.A.
PIONEER ELECTRONIC (EUROPE) N.V. Haven 1087, Keetberglaan 1, 9120 Melsele, Belgium
PIONEER ELECTRONICS ASIACENTRE PTE. LTD. 501 Orchard Road, #10-00 Lane Crawford Place, Singapore 0923

T - IZY JUNE 1998 Printed in Japan

1. SAFETY INFORMATION

This service manual is intended for qualified service technicians ; it is not meant for the casual do-it-yourselfer. Qualified technicians have the necessary test equipment and tools, and have been trained to properly and safely repair complex products such as those covered by this manual.
Improperly performed repairs can adversely affect the safety and reliability of the product and may void the warranty. If you are not qualified to perform the repair of this product properly and safely, you should not risk trying to do so and refer the repair to a qualified service technician.

WARNING
This product contains lead in solder and certain electrical parts contain chemicals which are known to the state of California to cause cancer, birth defects or other reproductive harm.

Health & Safety Code Section 25249.6 – Proposition 65

NOTICE
(FOR CANADIAN MODEL ONLY)
Fuse symbols (fast operating fuse) and/or (slow operating fuse) on PCB indicate that replacement parts must be of identical designation.

REMARQUE
(POUR MODÈLE CANADIEN SEULEMENT)
Les symboles de fusible (fusible de type rapide) et/ou (fusible de type lent) sur CCI indiquent que les pièces de remplacement doivent avoir la même désignation.

(FOR USA MODEL ONLY)

1. SAFETY PRECAUTIONS

The following check should be performed for the continued protection of the customer and service technician.

LEAKAGE CURRENT CHECK

Measure leakage current to a known earth ground (water pipe, conduit, etc.) by connecting a leakage current tester such as Simpson Model 229-2 or equivalent between the earth ground and all exposed metal parts of the appliance (input/output terminals, screwheads, metal overlays, control shaft, etc.). Plug the AC line cord of the appliance directly into a 120V AC 60Hz outlet and turn the AC power switch on. Any current measured must not exceed 0.5mA.



AC Leakage Test

ANY MEASUREMENTS NOT WITHIN THE LIMITS OUTLINED ABOVE ARE INDICATIVE OF A POTENTIAL SHOCK HAZARD AND MUST BE CORRECTED BEFORE RETURNING THE APPLIANCE TO THE CUSTOMER.

2. PRODUCT SAFETY NOTICE

Many electrical and mechanical parts in the appliance have special safety related characteristics. These are often not evident from visual inspection nor the protection afforded by them necessarily can be obtained by using replacement components rated for voltage, wattage, etc. Replacement parts which have these special safety characteristics are identified in this Service Manual.

Electrical components having such features are identified by marking with a ⚠ on the schematics and on the parts list in this Service Manual.

The use of a substitute replacement component which does not have the same safety characteristics as the PIONEER recommended replacement one, shown in the parts list in this Service Manual, may create shock, fire, or other hazards.

Product Safety is continuously under review and new instructions are issued from time to time. For the latest information, always consult the current PIONEER Service Manual. A subscription to, or additional copies of, PIONEER Service Manual may be obtained at a nominal charge from PIONEER.

2. EXPLODED VIEWS AND PARTS LIST

NOTES: ● *Parts marked by "NSP" are generally unavailable because they are not in our Master Spare Parts List.*
● *The ⚠ mark found on some component parts indicates the importance of the safety factor of the part. Therefore, when replacing, be sure to use parts of identical designation.*
● *Screws adjacent to ▼ mark on the product are used for disassembly.*

2.1 PACKING



● PACKING PARTS LIST

Mark	No.	Description	Part No.
NSP	1	Warranty Card	ARY7021
NSP	2	Bar Code Sheet	VRY1115
	3	Audio Cord	VDE1033
	4	Video Cord	VDE1048
	5	Nylon Clamp	VEC1988
NSP	6	Dry Cell Battery (LR6, AA)	VEM-013
	7	Operating Instructions (Basic Operations) (English)	VRB1185
	8	Operating Instructions (Applied Operations) (English)	VRB1208
	9	Remote Control Unit (For Business DVD)	VXX2553
NSP	10	Polyethylene Bag (50×70×0.03)	Z21-002
	11	Polyethylene Bag (230×340×0.03)	Z21-038
	12	Sheet	RHX1006
NSP	13	Cord Bag	VEG-012
	14	Pad F	VHA1212
	15	Pad R	VHA1213
	16	Partition Plate	VHB1062
	17	Packing Case	VHG1735
	18	Battery Cover	DNK2926
	19	Screw	AMZ30P080FZK

2.2 MAIN SECTION



● MAIN SECTION PARTS LIST

Mark	No.	Description	Part No.
	1	DVDM Assy	VWS1344
	2	SUBB Assy	VWG1925
	3	KEYB Assy	VWG1926
	4	HPIR Assy	VWG1927
	5	SPDB Assy	VWG1928
	6	PS2B Assy	VWG1941
	7	JACB Assy	VWV1594
	8	EXTB Assy	VWV1595
⚠	9	POWER SUPPLY Assy	VWR1288
	10	• • • • •	
	11	Flexible Cable (20P) (SPDB CN258 – DVDM CN102)	VDA1669
	12	Flexible Cable (06P) (PS2B CN801 – KEYB CN153)	VDA1670
	13	Flexible Cable (16P) (KEYB CN151 – SUBB CN101)	VDA1671
	14	Flexible Cable (24P) (JACB CN602 – SUBB CN102)	VDA1672
	15	Flexible Cable (10P) (EXTB CN751 – JACB CN653)	VDA1673
	16	Flexible Cable (07P) (SPDB CN251 – DVDM CN805)	VDA1674
	17	Flexible Cable (12P) (SPDB CN252 – DVDM CN107)	VDA1675
	18	Flexible Cable (14P) (DVDM CN105 – SUBB CN103)	VDA1676
	19	Flexible Cable (08P) (DVDM CN108 – SUBB CN201)	VDA1677
	20	Flexible Cable (17P) (JACB CN601 – DVDM CN802)	VDA1686
	21	• • • • •	
⚠	22	AC Power Cord (KU)	VDG1073
	23	AC Cord Stopper	VEC-201
	24	Housing Assy (14P) (POWER SUPPLY CN201 – DVDM CN101)	VKP2163
	25	Housing Assy (04P) (DVDM CN801 – SUBB CN301)	VKP2164
NSP	26	Loading Mechanism Assy	VWT1151
	27	Bolt	DBA1078
NSP	28	Locking Wire Saddle	DEC1305
NSP	29	Nylon Rivet	DEC1644
NSP	30	Card Spacer	DEC1772
NSP	31	PCB Holder	PNW2100
	32	Foot Assy	PXA1201
	33	Tape (G)	REH1010
	34	Tray Stopper Spring	VBH1277
	35	Radiation Sheet	VEB1279
	36	Radiation Sheet (Silicone Rubber)	VEB1285
	37	• • • • •	
	38	Sheet	VEC1999
	39	• • • • •	
	40	Rear Panel	VNA1930
	41	Bonnet	VNA1931
NSP	42	Main Chassis	VNB1037
	43	Sub Chassis	VNB1038
	44	Clamper Plate	VNE2068
	45	Bridge	VNE2069
	46	SYPS Stay	VNE2128
	47	Shield Stay F	VNE2129
	48	Shield Stay R	VNE2130
	49	Center Stay	VNE2131
	50	PCB Stay	VNE2133
	51	Heat Sink	VNE2134
	52	Cover	VNE2147
	53	Tray	VNL1731
	54	Clamper	VNL1738
	55	Tray Stopper	VNL1739
	56	Lens	PNW1257
	57	LED Lens	PNW2019
	58	Earth Spring	VBH1301
	59	Screen	VEC1977
	60	Earth Plate	VNE2027
	61	IR Window	VNK2246
	62	Volume Knob	VNK3124
	63	Illumination Holder	VNK3917
	64	Illumination Lens	VNK4168
	65	Front Panel	VNK4222
	66	DVD Door	VNK4224
	67	Operation Key Assy	VXA2360
	68	Flexible Cable (14P) (DVDM CN803 – SUBB CN302)	VDA1676
	69	65 Label	ORW1069
NSP	70	Label	VRW-348
NSP	71	Fuse Caution Label (G)	VRW-548
	72	Tray Label	VRW1628
	73	Fuse Caution Label	VRW1693
NSP	74	Label	VRW1735
	75	Screw	BCZ30P080FZK
	76	Screw	BBZ30P080FMC
	77	Screw	BBZ30P100FMC
	78	Screw	BCZ40P060FZK
	79	Screw	BPZ26P080FZK
	80	Screw	PMZ40P080FMC
NSP	81	Cord Stopper	ZCB-069Z

2.3 LOADING MECHANISM ASSY



● LOADING MECHANISM ASSY PARTS LIST

Mark	No.	Description	Part No.
	1	Servo Mechanism Assy-S	VXX2567
	2	Screw	DBA1006
	3	Drive Cam	VNL1736
	4	Drive Gear	VNL1735
	5	Lock Plate	VNL1820
	6	Loading Base	VNL1730
	7	Rubber Belt	VEB1260
	8	Gear Pulley	VNL1733
NSP	9	LOSB Assy	VWG1758
	10	Loading Gear	VNL1734
	11	Loading Motor Assy	VXX2505
	12	DC Motor	PXM1027
	13	Motor Pulley	PNW1634
NSP	14	LOMB Assy	VWG1757
	15	Connector Assy (2P) (LOMB CN301 – SPDB CN254)	PG02KK-E20
	16	Screw	VBA1055
	17	Screw	Z39-019
	18	Flexible Cable (7P) (LOSB CN202 – SPDB CN253)	VDA1571
	19	Connector Assy (4P) (LOSB CN201 – INSB CN101)	PG04MM-E12
	20	Stopper	DNH2076

2.4 SERVO MECHANISM ASSY

• **Top View** • **Bottom View**



● SERVO MECHANISM ASSY PARTS LIST

Mark	No.	Description	Part No.
	1	Spindle Motor Assy	VXX2580
	2	Magnet Holder Assy	VXX2507
NSP	3	Magnet	VYM1024
NSP	4	Magnet Holder	VNE2070
	5	Centering Ring	VNL1746
	6	Centering Spring	VBH1278
NSP	7	Disc Table	VNL1747
NSP	8	Motor	VXM1073
	9	Screw	JGZ17P028FMC
	10	Sub Guide Bar	VLL1489
	11	Guide Bar	VLL1488
	12	Mechanism Base	VNL1800
	13	• • • • •	
	14	• • • • •	
	15	Slider	VNL1745
	16	Hold Spring	VNC1011
	17	Pickup Assy	VWY1046
	18	Floating Rubber	DEB1315
	19	Float Base	VNL1732
	20	Gear D	VNL1766
	21	Gear Spring	VBH1279
	22	Gear E	VNL1767
	23	Gear F	VNL1768
	24	Motor (SLIDER)	VXM1062
NSP	25	INSB Assy	VWG1759
	26	Screw	PBZ20P050FMC
	27	Flexible Cable (20P) (SPDB CN257 – Pickup Assy)	VDA1569
	28	• • • • •	
	29	Table Sheet	DEC2040
	30	Screw	PBA1048
	31	• • • • •	
	32	Flexible Cable (11P) (SPDB CN255 – SPDL Motor)	VDA1682

3. SCHEMATIC DIAGRAM

3.1 OVERALL CONNECTIONS, LOSB, LOMB, INSB and PICKUP ASSEMBLIES



Note : When ordering service parts, be sure to refer to "EXPLODED VIEWS and PARTS LIST" or "PCB PARTS LIST".



3.2 SPDB ASSY


D SPDB ASSY
(VWG1928)
TO SPINDLE MOTER ASSY
CN255
VKN1187-
NKF11D
IC251 BA6849FP
IEP30B
V+5S
V+12M
NHRB03
R256 (1/4) 2.2
R257 (1/4) 2.2
R258 (1/4) 2.2
R255 2.2K
R251 100
R252 4.7K
R254 0
1 mm pitch FFC
CN251
VKN1211-
NKF07D
F 1/3
CN805
GNDM
CN253
VKN1183-
NKF07D
A
CN202
B
CN301
CN254
B2B-PH-K-S
KMNB02
CN252
VKN1216-
1 mm pitch FFC
NKF12D
F 1/3
CN107
GNDS
Shoot <--> Open
S251
VSH1009-
NSAA02
0.5 mm pitch FFC
CN257
VKN1460-A-TFB
KF1H20
0.5 mm pitch FFC
CN258
VKN1352-A-TBB
KFID20
TO PICKUP ASSY
F 1/3
CN102
TRKGDRV
GND
1pin
: RF SIGNAL ROUTE
(F) : FOCUS SERVO LOOP LINE
(T) : TRACKING SERVO LOOP LINE
(S) : SLIDER SERVO LOOP LINE

3.3 POWER SUPPLY ASSY

《NOTE OF SPARE PARTS IN POWER SUPPLY ASSY》

- In case of repairing, use the described parts only to prevent an accident.
- Please write the red √ mark on the board when the primary section of POWER SUPPLY Assy is repaired.
- Please take care to keep the space, not touching other parts when replacing the parts.



CAUTION : FOR CONTINUED PROTECTION AGAINST RISK OF FIRE, REPLACE ONLY WITH SAME TYPE NO. 49101.5, MFD BY LITTELFUSE INC. FOR P211 AND 491001 MFD. BY LITTELFUSE INC. FOR P311.

3.4 DVDM ASSY (1/3)




: RF SIGNAL ROUTE
(ROM) : ROM DATA SIGNAL ROUTE
(F) : FOCUS SERVO LOOP LINE
(T) : TRACKING SERVO LOOP LINE
(S) : SLIDER SERVO LOOP LINE
IC501
PD4889A
IC201
LC78650NE
IC502
SRM2B256SLMX70
IC503
TC74HC573AF
IC504
TC74VHC20FT
IC505(1/2)
TC74VHC139FT
IC505(2/2)
TC74VHC139FT
IC506
TC74VHCT245AFT
VKF1001
TP200
F 3/3
F 2/3
XRESET,DOUT,SBSY,
PW,SFSY,SBCK,LRSY,
ROMCK,ROMXA,MON,
C2F,FG
CN251
CN805
VKN1299
VREF
FG
MON
SPDO
V+5S
V+12M
GNDM
DUTY50
SPDL
TILTE
LD-ON

3.5 DVDM ASSY (2/3)




: AUDIO SIGNAL ROUTE
(ROM) : ROM DATA SIGNAL ROUTE
IC702
HM514800CJ-7
IC817
TC74VHCT541AFT
IC701
LSI11
PD4833A
SDATA
MONITOR OUTPUT
SERVO
DSP
MECH CPU
VKN1418
CN105
G1/2
CN103
F 1/3
F 2/3
F 3/3

3.6 DVDM ASSY (3/3)




F 2/3
HIBSEL,48/X44,XRESET,XLT3,XAMUTE,
SSCK,SSO,DOLV CD,XCSDOLV
F 2/3
MAIN
K CN601
G 2/2 CN302
VKN1421
CN802
VKN1418
CN803
: AUDIO SIGNAL ROUTE
: ROM DATA SIGNAL ROUTE
: COMPOSITE VIDEO SIGNAL ROUTE
: Y SIGNAL ROUTE
: C SIGNAL ROUTE

3.7 SUBB ASSY (1/2)




V+5D
SYNC SEP
IC201
CS OUT
VIN
VS
GND
VCC
ODD
RSET
BF
LM1881M-TBB
IEP08B
R204 100
R203 100
R202 620
NP
C206 1/50
C207 470P
C204 0.1
C203 47/16
C205 0.1
R201 680K
GNDD
J101
BOARD IN CONECTOR
ODD
TO CN302
G 2/2
: AUDIO SIGNAL ROUTE
V+5E
V+5EL
R148 10k
R1001
RA4C103J-T
C106 0.01
C105 47/16
HD0BD0
D101
RB400D
500mA
D102
1SS355-TRB
L803
QTL1015- -T
CN103
VKN1190-
-27V
AC1
AC2
POWER ON
EVER 5V
(5.45±0.15V)
GNDD
S OUT
S IN
S CLK
XRESET
LT1
XREADY
SELIR
IR
NKF14D
F 2/3
CN105
R115 220
R116 220
R117 330
R135 100
GNDD
µCOM-GND
R1004 100K
R119 100K
R118 100K
REAL-TIME CLK IC
IC102
VSS1122- -TLB
X102
INT
XIN
XOUT
VSS
VDD
SIO
SCK
CS
S-3511AEFS-TBB
NIE08J
32.768KHz
C107 4P CH
C108 0.1
Super Capa Backup
R137 470
C110 DCH1037- 0.22F
R121 100
C111 0.1
GNDC
R127 0
VNF1084- -T
KN101
KN102
Chassis GND
System Reset IC
IC103
NC
NC
NC
GND
VCC
RESET
C
M51953BFP-TFB
IEP08B
R126 22K
C115 0.1

3.8 SUBB ASSY (2/2)



: AUDIO SIGNAL ROUTE



3.9 KEYB, HPIR and PS2B ASSEMBLIES







KEYB ASSY
- S151 : POWER STANDBY/ON (⏻)
- S152 : STILL/STEP(◀II)
- S153 : STILL/STEP(II▶)
- S154 : DISPLAY
- S155 : STOP OPEN/CLOSE(■/⏏)
- S156 : SCAN/SKIP(◀◀/⏮)
- S157 : SCAN/SKIP(▶▶/⏭)
- S158 : PLAY/PAUSE(▷/▯▯)

3.10 JACB ASSY




V+5P
IC611 (4/6)
TC74HCU04AF
RTF1167
L802
L611
PTL1003-
LWWA03
JA610 VKB1077-
AC3/PCM
NJMA07
IC611 (5/6)
IC611 (6/6)
IC611(1/6)
IC611(2/6)
IC611(3/6)
GNDD1
GNDV
(CHASSIS GND)
(Y)
Y
8V
LETTER
(COM)
(C)
DTC124EK
DTA124EK
2SC1740S(QRS)-T
S2
TERMINAL
JA602
VKN1072-
JDNA16
VIDEO
2PD601A(QR)-TLB
RF PIN JACK
JA603
VKB1068-
VIDEO
DC
AUDIO
V+5D1
JCOA01
JA604(1/3)
JKPA57
R
AUDIO OUT
L
JA604 (2/3)
VKB1046-
JA604 (3/3)
2SD2114K (VW)-TLB
2PB709A(QR)-TLB
GNDA1
: AUDIO SIGNAL ROUTE
: COMPOSITE VIDEO SIGNAL ROUTE
: Y SIGNAL ROUTE
: C SIGNAL ROUTE

3.11 EXTB ASSY

L EXTB ASSY (VWV1595)



4. PCB CONNECTION DIAGRAM

NOTE FOR PCB DIAGRAMS :

1. Part numbers in PCB diagrams match those in the schematic diagrams.
2. A comparison between the main parts of PCB and schematic diagrams is shown below.

Symbol In PCB Diagrams	Symbol In Schematic Diagrams	Part Name
B C E	B C E B C E	Transistor
B C E	B C E B C E	Transistor with resistor
D G S	D G S D G S	Field effect transistor
		Resistor array
		3-terminal regulator

3. The parts mounted on this PCB include all necessary parts for several destinations.
   For further information for respective destinations, be sure to check with the schematic diagram.
4. View point of PCB diagrams.



4.1 LOSB, LOMB and INSB ASSEMBLIES





4.2 SPDB ASSY



SIDE A



SIDE B

(VNP1648-B)

4.3 POWER SUPPLY ASSY

E POWER SUPPLY ASSY



F CN101

SIDE A

4.4 DVDM ASSY



- This PCB is a four-layered board.
  Middle layer is mainly connected to Vcc and GND.

F DVDM ASSY



(VNP1624-C)

SIDE B

- This PCB is a four-layered board.
  Middle layer is mainly connected to Vcc and GND.

4.5 SUBB ASSY



SIDE A

G SUBB ASSY



(VNP1648-B)

SIDE B

4.6 KEYB, HPIR and PS2B ASSEMBLIES



SIDE A

I HPIR ASSY



(VNP1648-B)

H KEYB ASSY



J PS2B ASSY



SIDE B

4.7 JACB ASSY


K JACB ASSY
K JACB ASSY
Q637
Q636
Q682
Q683
L
CN751
F
CN802
G
CN102
IC701
Q701
Q708
(VNP1648-B)
SIDE A
SIDE B
Q651
Q654
Q631
Q635
Q681
IC611
Q552
Q551
Q452
Q451

4.8 EXTB ASSY



SIDE A



(VNP1648-B)

SIDE B

5. PCB PARTS LIST

NOTES: ●*Parts marked by "NSP" are generally unavailable because they are not in our Master Spare Parts List.*
●*The ⚠ mark found on some component parts indicates the importance of the safety factor of the part. Therefore, when replacing, be sure to use parts of identical designation.*
●*When ordering resistors, first convert resistance values into code form as shown in the following examples.*
Ex.1 When there are 2 effective digits (any digit apart from 0), such as 560 ohm and 47k ohm (tolerance is shown by J=5%, and K=10%).
560 Ω → 56 × 10¹ → 561 ..... RD1/4PU 5 6 1 J
47k Ω → 47 × 10³ → 473 ..... RD1/4PU 4 7 3 J
0.5 Ω → R50 ..... RN2H R 5 0 K
1 Ω → 1R0 ..... RS1P 1 R 0 K
Ex.2 When there are 3 effective digits (such as in high precision metal film resistors).
5.62k Ω → 562 × 10¹ → 5621 ..... RN1/4PC 5 6 2 1 F

Mark	No.	Description	Part No.

LIST OF ASSEMBLIES

NSP		LOAB ASSY	VWM1690
NSP		├ LOSB ASSY	VWG1758
NSP		└ LOMB ASSY	VWG1757
NSP		INSB ASSY	VWG1759
NSP		FCJB ASSY	VWM1819
		├ SUBB ASSY	VWG1925
		├ KEYB ASSY	VWG1926
		├ HPIR ASSY	VWG1927
		├ SPDB ASSY	VWG1928
		├ PS2B ASSY	VWG1941
		├ JACB ASSY	VWV1594
		└ EXTB ASSY	VWV1595
		DVDM ASSY	VWS1344
⚠		POWER SUPPLY ASSY	VWR1288

LOAB ASSY

OTHERS

		PC BOARD LOAB	VNP1572

A LOSB ASSY

SWITCH

	S201		VSK1011

OTHERS

	CN201	MT CONNECTOR 4P	173979-4
	CN202	7P FFC CONNECTOR	VKN1211

B LOMB ASSY

OTHERS

	CN301	KR CONNECTOR	B2B-PH-K-S

C INSB ASSY

SWITCH

	S101		DSG1017

OTHERS

	CN101	MT CONNECTOR 4P	173981-4
		PC BOARD INSB	VNP1593

D SPDB ASSY

SEMICONDUCTOR

	IC251		BA6849FP

SWITCH

	S251		VSH1009

CAPACITORS

	C253,C255		CEAT470M16
	C262-C264		CKSQYB333K50
	C257		CKSQYB821K50
	C258		CKSQYB822K50
	C251		CKSQYF103Z50
	C252,C254,C256		CKSQYF104Z25
	C259-C261		CKSQYF105Z16

RESISTORS

	R256-R258		RS1/4S2R2J
	Other Resistors		RS1/10S□□□J

OTHERS

	CN254	KR CONNECTOR	B2B-PH-K-S
		PCB BINDER	DEF1012
	CN253	7P FFC CONNECTOR	VKN1183
	CN255	11P FFC CONNECTOR	VKN1187
	CN251	7P FFC CONNECTOR	VKN1211
	CN252	12P FFC CONNECTOR	VKN1216
	CN258	20P FFC CONNECTOR	VKN1352
	CN257	20P FFC CONNECTOR	VKN1460

Mark	No.	Description	Part No.
	E POWER SUPPLY ASSY		
	SEMICONDUCTORS		
⚠	IC201		AN1431T
⚠	D106		PC817
⚠	IC411		VZF1048
⚠	IC711		VZF1060
	Q511		2SC1740S
⚠	Q102		2SC3377
⚠	Q101,Q103		VZF1049
⚠	D511		10ELS2
⚠	D105		1SS270A
	D512,D514		1SS270A
⚠	D104		MTZJ2.7B
	D513		MTZJ8.2B
⚠	D311		S3L20U
⚠	D102		UK1V26
⚠	D101		VZF1044
⚠	D108		VZF1045
⚠	D110		VZF1045
⚠	D211		VZF1058
⚠	D411		VZF1059
⚠	D212		VZF1061
	OTHERS		
⚠	F101	FUSE(2A)	REK1078
⚠	P311	FUSE(1A)	VEK1041
⚠	P211	FUSE(1.5A)	VEK1048
	F DVDM ASSY		
	SEMICONDUCTORS		
	IC171		BA10393F
	IC151		BA6797FP
	IC813		CY2081SL-611
	IC702		HM514800CJ-7
	IC101		LA9700M
	IC201		LC78650NE
	IC802		MB811171622A-100FN
	IC801		MB86371
	IC815,IC816		MC14577CF
	IC271,IC302		NJM2100M
	IC203		NJM2107F
	IC601		PD3381A
	IC701		PD4833A
	IC501		PD4889A
	IC602		PDK026C
	IC502		SRM2B256SLMX70
⚠	IC401		TA78M08F
	IC202,IC204,IC206		TC4W53F
	IC604		TC551001BFL-85
	IC503		TC74HC573AF
	IC804		TC74HCT541AF
	IC303		TC74HCU04AF
	IC807,IC808		TC74LCX245FT
	IC821		TC74VHC00FT
	IC814,IC820		TC74VHC02FT
	IC505,IC605		TC74VHC139FT
	IC504		TC74VHC20FT
	IC805,IC806,IC809		TC74VHC541FT
	IC506		TC74VHCT245AFT
	IC817		TC74VHCT541AFT

Mark	No.	Description	Part No.
	IC824		TC7S32F
	IC811,IC818,IC819		TC7SHU04F
	IC810		TC7WU04F
	IC301		TLC5540INS
	IC603		VYW1540
⚠	Q401		2SB1260
	Q108		HN1K03FU
	Q455,Q831,Q832,Q851,Q852		IMT1A
	Q871,Q872		IMT1A
	Q103,Q402,Q873		IMX1
	Q102,Q104,Q291,Q301		IMZ1A
	Q106,Q603		PDTA114EK
	Q107,Q109,Q602		PDTC114EK
	Q601,Q771,Q772		PDTC114TK
	D301		KV1410
	D171,D172		MA152WK
	D601		RB501V-40
	COILS AND FILTERS		
	F771,F778,F779		DTF1067
	L941,L942,L945,L946		QTL1011
	F896		VTF1077
	F801		VTF1098
	F401-F406		VTH1037
	L301(1.5µH)		VTL1059
	L101,L302(10µH)		VTL1061
	L802,L803		VTL1067
	L335,L340,L342		VTL1074
	L777,L780-L787,L895		VTL1075
	L897-L899		VTL1075
	CAPACITORS		
	C623		CCSRCH100D50
	C152,C208,C291,C612,C613		CCSRCH101J50
	C700,C735,C737,C739		CCSRCH101J50
	C897,C898		CCSRCH101J50
	C111,C139,C215,C231,C232		CCSRCH151J50
	C248		CCSRCH151J50
	C125,C148,C329		CCSRCH180J50
	C112,C118		CCSRCH220J50
	C121,C130,C199,C319,C324		CCSRCH330J50
	C120		CCSRCH331J50
	C310,C323,C327		CCSRCH470J50
	C230		CCSRCH471J50
	C126,C331,C838		CCSRCH560J50
	C127,C330,C863,C873,C882		CCSRCH5R0C50
	C160		CCSRCH680J50
	C401		CEV101M10
	C101,C104,C201,C325,C601		CEV101M6R3
	C701,C704,C706,C801		CEV101M6R3
	C803,C804,C813-C815,C826		CEV101M6R3
	C901		CEV101M6R3
	C123,C158,C412,C414		CEV220M16
	C835,C895		CEV221M4
	C131,C135,C205,C206,C301		CEV470M6R3
	C303,C404,C406,C408,C410		CEV470M6R3
	C501,C504,C832,C836,C841		CEV470M6R3
	C887		CEV470M6R3
	C211		CKSQYB104K25
	C109,C124,C216,C220,C229		CKSQYB105K10
	C234,C275,C308,C326		CKSQYB105K10
	C332,C333,C730,C731		CKSQYB105K10

Mark	No.	Description	Part No.
	C818,C823,C828		CKSQYF105Z16
	C213,C292,C309,C321		CKSRYB102K50
	C105,C106,C108,C146,C147		CKSRYB103K50
	C151,C154-C157,C161,C207		CKSRYB103K50
	C217,C221,C247,C276,C318		CKSRYB103K50
	C320,C620,C705,C722,C772		CKSRYB103K50
	C859		CKSRYB103K50
	C143,C162-C165,C223,C224		CKSRYB104K16
	C242,C273,C274,C311,C312		CKSRYB104K16
	C315		CKSRYB104K16
	C141		CKSRYB222K50
	C328		CKSRYB223K25
	C271		CKSRYB472K50
	C122		CKSRYB473K16
	C102,C103,C113,C129		CKSRYF104Z16
	C132-C134,C136,C137,C159		CKSRYF104Z16
	C166,C191,C202-C204,C209		CKSRYF104Z16
	C214,C218,C219,C222		CKSRYF104Z16
	C226-C228,C235,C237,C241		CKSRYF104Z16
	C246,C302,C304,C305,C317		CKSRYF104Z16
	C322,C402,C403,C405,C407		CKSRYF104Z16
	C409,C411,C413,C415		CKSRYF104Z16
	C502,C503,C505-C509		CKSRYF104Z16
	C602-C605,C608-C611		CKSRYF104Z16
	C614,C615,C617,C621,C622		CKSRYF104Z16
	C702,C703,C707-C721		CKSRYF104Z16
	C732-C734,C736,C738		CKSRYF104Z16
	C740-C742,C771,C791,C800		CKSRYF104Z16
	C802,C805-C812,C816,C817		CKSRYF104Z16
	C819-C822,C824,C825,C827		CKSRYF104Z16
	C829,C830,C833,C834,C837		CKSRYF104Z16
	C839,C840,C842-C848,C851		CKSRYF104Z16
	C861,C862,C867,C871,C872		CKSRYF104Z16
	C876,C878,C881,C883		CKSRYF104Z16
	C888-C890,C902-C905,C911		CKSRYF104Z16
	C852,C855,C857,C858 (2.2µF/6.3V)		VCG1030
	C922-C924(2.2µF/6.3V)		VCG1030
	VC301(40pF)		VCM1010

RESISTORS

	R752	RA4C101J
	R507,R508,R624,R628,R633	RA4C103J
	R703,R704,R717,R718	RA4C103J
	R745,R746,R761,R762,R792	RA4C103J
	R812,R813	RA4C103J
	R137,R501,R502,R505,R506	RA4C220J
	R604-R607,R712,R713,R719	RA4C220J
	R724,R748,R749,R791	RA4C220J
	R802,R803,R808	RA4C220J
	R602,R603,R610,R613,R618	RA4C470J
	R101,R11-R14,R141	RS1/10S0R0J
	R15-R17,R171,R18	RS1/10S0R0J
	R201-R203,R300,R319,R333	RS1/10S0R0J
	R411-R413,R701,R775,R776	RS1/10S0R0J
	R891,R893,R920,R921	RS1/10S0R0J
	R935,R936,R961	RS1/10S0R0J
	R205	RS1/10S101J
	R835,R839,R855,R859,R875	RS1/16S1001F
	R881	RS1/16S1001F
	R834,R854,R874	RS1/16S1201F

Mark	No.	Description	Part No.
	R823-R825		RS1/16S1500F
	R117,R118		RS1/16S1501F
	R126		RS1/16S1502F
	R241,R247		RS1/16S2202F
	R110,R153,R155,R173,R174		RS1/16S2702F
	R213,R228,R229,R248		RS1/16S2702F
	R152,R156,R158-R164		RS1/16S4702F
	R167-R170,R172,R175,R194		RS1/16S4702F
	R227		RS1/16S4702F
	VR801(1kΩ)		VCP1125
	Other Resistors		RS1/16S□□□J

OTHERS

	CN101 PH CONNECTOR	S14B-PH-SM3
	CN801 PH CONNECTOR	S4B-PH-SM3
	TP100,TP200,TP300,TP400 CHECKER CHIP	VKF1001
	CN805 7P FFC CONNECTOR	VKN1299
	CN108 8P FFC CONNECTOR	VKN1300
	CN201 B TO B CONNECTOR 14P	VKN1324
	CN107 12P FFC CONNECTOR	VKN1416
	CN105,CN803 14P FFC CONNECTOR	VKN1418
	CN802 17P FFC CONNECTOR	VKN1421
	CN102 20P FFC CONNECTOR	VKN1445
	KN1-KN3 EARTH METAL FITTING	VNF1109
	LABEL	VRW1634
	X602 CHIP CERAMIC RESONATOR(20MHz)	VSS1114
	X501 CHIP CERAMIC RESONATOR(10MHz)	VSS1115
	44P IC SOCKET	VKH1012

G SUBB ASSY

SEMICONDUCTORS

	IC401,IC402,IC501,IC502	BA4560F
	IC201	LM1881M
	IC103	M51953BFP
	IC301	NJM2100M
	IC351	PD2026B(L)
	IC101	PD4954A
	IC102	S-3511AEFS
	IC302	TC4W53F
	IC305-IC307	TC7S02F
	IC308	TC7S04F
	IC303,IC304	TC7WU04F
	Q201,Q401,Q402,Q501,Q502	DTC124EK
	D102,D361,D362	1SS355
	D301	KV1851
	D101	RB400D
	D351,D352	UDZS6.2B

COILS

	L351-L353	LFA220J
	L803,L901-L912	QTL1015
	L301,L302,L804	VTL1019

Mark	No.	Description	Part No.
CAPACITORS			
	C307		CCSQCH160J50
	C308,C309		CCSQCH180J50
	C318,C319,C405,C406		CCSQCH470J50
	C505,C506		CCSQCH470J50
	C207		CCSQCH471J50
	C107		CCSQCH4R0C50
	C404,C504		CCSQCH820J50
	C201		CEJA100M16
	C359,C361		CEJA331M6R3
	C105,C203,C310,C321,C353		CEJA470M16
	C363,C364,C403,C407,C408		CEJA470M16
	C412,C503,C507,C508		CEJA470M16
	C511,C512		CEJA470M16
	C206,C303		CEJANP1R0M50
	C355		CEV101M10
	C101		CEV470M16
	C103,C104		CKSQYB102K50
	C102,C106,C121,C305,C357		CKSQYF103Z50
	C401,C409,C501,C509		CKSQYF103Z50
	C109,C111,C115,C202		CKSQYF104Z25
	C204,C205,C302,C304		CKSQYF104Z25
	C311-C317,C320,C322,C323		CKSQYF104Z25
	C352,C354,C356,C358,C360		CKSQYF104Z25
	C362,C402,C410,C502,C510		CKSQYF104Z25
	C208		CKSQYF105Z16
	C366		CKSQYF473Z50
	C301		CQMBA332J50
	C110(0.22F)		DCH1037
RESISTORS			
	R1001-R1003		RA4C103J
	R408,R409,R508,R509		RN1/10SE4702D
	VR301(10kΩ)		VCP1156
	Other Resistors		RS1/10S□□□J
OTHERS			
	CN301	KR CONNECTOR	B4B-PH-K-S
		PCB BINDER	DEF1012
		PCB BINDER	VEF1040
	CN201	8P FFC CONNECTOR	VKN1184
	CN103,CN302		VKN1190
		14P FFC CONNECTOR	
	CN101	16P FFC CONNECTOR	VKN1192
	CN102	24P FFC CONNECTOR	VKN1200
	KN101,KN102,KN361		VNF1084
		EARTH METAL FITTING	
	X302		VSS1084
		CHIP CRYSTAL RESONATOR(16.93MHz)	
	X101	CERAMIC RESONATOR (5MHz)	VSS1104
	X301		VSS1121
		CHIP CRYSTAL RESONATOR(18.432MHz)	
	X102		VSS1122
		CHIP CRYSTAL RESONATOR(32.768kHz)	

Mark	No.	Description	Part No.
H KEYB ASSY			
SEMICONDUCTORS			
	IC151		BU2090F
	IC152		NJM2930L05
	Q153		2SA1036K
	Q152		DTA124EK
	Q154		DTC124EK
	D159		BR1112H(CDEF)
	D158,D160		PG1112H-430
	D161		RB400D
	D154,D155,D157		SLP3118C51H
	D153		SLP6118C51H
	D152		VRPG5615S
COIL			
	L151		VTL1019
SWITCHES			
	S151-S157,S159		RSG1030
CAPACITORS			
	C155		CEV101M10
	C151		CEV470M6R3
	C152,C153,C156,C157		CKSQYF104Z25
RESISTORS			
	All Resistors		RS1/10S□□□J
OTHERS			
	CN152	FJ CONNECTOR 7P	07PL-FJ
	CN153		52492-0620
		FFC BOTTOM CONNECTOR 6P	
	CN151	16P FFC CONNECTOR	VKN1308
I HPIR ASSY			
SEMICONDUCTOR			
	D191		1SS355
COILS AND FILTER			
	L181-L183,L187,L191-L193		QTL1015
	F191		VTH1009
CAPACITORS			
	C182,C183		CCSQCH101J50
	C192		CEJA101M10
	C193		CKSQYF104Z25
	C181,C191 (1000pF/18V)		VCX1001
RESISTORS			
	VR181(0.5kΩ)		VCS1042
	Other Resistors		RS1/10S□□□J
OTHERS			
	CN191	FJ CONNECTOR 7P	07R-FJ
	JA191	MINI JACK	AKN7008
	Q191	REMOTE RECEIVER UNIT	GP1U26X
	JA181	MINI JACK	VKN1449

Mark	No.	Description	Part No.
J		**PS2B ASSY**	
		SEMICONDUCTORS	
	D801-D808		1SS355
		FILTERS	
	F801-F804		VTH1039
		CAPACITORS	
	C801-C804		CCSQCH101J50
	C805		CKSQYF104Z25
		RESISTORS	
	All Resistors		RS1/10S□□□J
		OTHERS	
	CN801	6P FFC CONNECTOR	52044-0645
	JA801	6P MINI DIN SOCKET	VKN1450
		PCB HOLDER	VNE2146
K		**JACB ASSY**	
		SEMICONDUCTORS	
	IC701		MAX202ESE
	IC611		TC74HCU04AF
	Q451,Q551		2PB709A
	Q654		2PD601A
	Q636,Q637,Q682,Q683		2SC1740S
	Q452,Q552		2SD2114K
	Q632,Q634,Q635,Q653,Q681		DTA124EK
	Q701-Q708		DTA124EK
	Q631,Q633,Q652		DTC124EK
	D702		1SS355
	D701		UDZS5.1B
		COILS AND FILTERS	
	L610,L681		LFA220J
	L611		PTL1003
	L802		RTF1167
	F701-F704		VTH1039
	L701		VTL1019
		CAPACITORS	
	C687		CCSQCH471J50
	C611,C613		CEAT101M10
	C634,C684		CEAT102M6R3
	C689		CEJA470M16
	C701		CEV101M10
	C614		CKSQYF103Z50
	C601-C603,C612,C616,C617		CKSQYF104Z25
	C632,C653,C655,C682,C688		CKSQYF104Z25
	C690,C702-C707		CKSQYF104Z25
	C451,C551		CQMBA332J50
		RESISTORS	
	R701		RA4C101J
	R613,R642,R657,R687		RS1/10S75R0F
	Other Resistors		RS1/10S□□□J

Mark	No.	Description	Part No.
		OTHERS	
	JA702	15P D-SUB SOCKET	DKN1111
	JA604	2P PIN JACK	VKB1046
	JA603	RF PIN JACK	VKB1068
	JA610	1P PIN JACK	VKB1077
	JA602	4P MINI DIN SOCKET	VKN1072
	CN653	10P FFC CONNECTOR	VKN1186
	CN601	17P FFC CONNECTOR	VKN1309
	CN602	24P FFC CONNECTOR	VKN1316
		SCREW PLATE	VNE1948
L		**EXTB ASSY**	
		SEMICONDUCTORS	
	Q901		2SC1740S
	D901,D902		1SS355
		SWITCH	
	S901		VSH1009
		CAPACITORS	
	C751,C902		CEAT470M16
	C901		CEJANP220M10
	C752,C753,C903		CKSQYF104Z25
		RESISTORS	
	R772,R792		RS1/10S5600F
	R773,R793		RS1/10S8200F
	Other Resistors		RS1/10S□□□J
		OTHERS	
	CN751	10P FFC CONNECTOR	VKN1302
	JA753	BNC JACK	VKN1447
		SCREW PLATE	VNE1948

6. ADJUSTMENT

6.1 ADJUSTMENT ITEMS AND LOCATION

■ Adjustment Points (PCB Part)

DVDM ASSY



SUBB ASSY



■ Adjustment Items

[Mechanical Part]

❶ Tangential Skew and Radial Skew Coarse Adjustment

❷ DVD Jitter Adjustment

[Electrical Part]

① 18MHz Master Clock Adjustment

② VCO Offset Adjustment

③ Video Output Level Adjustment

■ Adjustment Points (Mechanism Part)



Note 1:
Remove the tray when adjusting the tangential and radial adjustment screws.

Note 2:
After the adjustment, stabilize the screw with an adhesive.

6.2 JIGS AND MEASURING INSTRUMENTS

 CD test disc (ABEX-784)	 DVD test disc (DVD-MJK1)	 ⊖ Screwdriver (medium)	 ⊖ Screwdriver (small)
 ⊖ Precise screwdriver	 ⊕ Screwdriver (large)	 ⊕ Screwdriver (medium)	 Dual-trace oscilloscope (with delay) Frequency band ≥ 40MHz
 Frequency counter Display digit ≥ 8-digit	 TV monitor	 Test mode remote control unit (GGF1067)	
 Jitter Meter	 Equalizer Unit		

6.3 TEST MODE

TEST MODE: ON



TEST MODE: DISC SET

• **With TRAY**

<TRAY OPEN>

<TRAY CLOSE>



TEST MODE: PLAY

<TRACKING OFF PLAY>



<TRACKING ON PLAY>



TEST MODE: OFF



6.4 NECESSARY ADJUSTMENT POINTS

When	Adjustment Points	
■ EXCHANGE MECHANISM ASSY PARTS		
Exchange pickup	Mechanical point	❶,❷
	Electric point	———
Exchange spindle motor	Mechanical point	———
	Electric point	———
■ EXCHANGE PCB ASSY		
Exchange board SUBB ASSY	Mechanical point	———
	Electric point	———
	Note : ① is adjusted already.	
Exchange board DVDM ASSY	Mechanical point	———
	Electric point	———
	Note : ② and ③ are adjusted already.	

6.5 MECHANICAL ADJUSTMENT

① Tangential Skew and Radial Skew Coarse Adjustment



② DVD Jitter Adjustment



6.6 ELECTRICAL ADJUSTMENT

① 18MHz Master Clock Adjustment



② VCO Offset Adjustment



③ Video Output Level Adjustment



6.7 OPERATIONS IN THE TEST MODE

■ Test Mode Remote Control Unit (GGF1067)



■ TV Monitor Display



First screen display

Note : Switch the first and second screen by pressing the [DISPLAY] key on the remote control unit.



Second screen display (at lower right portion of the screen)

7. GENERAL INFORMATION

7.1 DISASSEMBLY







3


Short
①
Short SW
② × 4
Loading Mechanism Assy
③

4


① × 2
〈Remove the Servo Mechanism〉
〈Remove the Flexible Cable of PU〉
②
③
Cause the lock of the connector.
〈Remove the Flexible Cable from Float Base〉
④
〈Remove the PU〉
Be careful not to bend this plate spring during installation / removal of PU.
⑤
Move the tab
⑥
Remove the Gear
⑦ Move the hook to remove the Guide Bar.
Guide Bar

5


① × 2
②
① × 2
③
④
Diagnose the POWER SUPPLY ASSY

7.2 BLOCK DIAGRAM



8. PANEL FACILITIES AND SPECIFICATIONS

■ Front panel



■ Rear panel



■ Interface Connector Terminal

1. Show the terminal arrangement of interface connector (D-SUB 15 pin) in the following.

Pin No.	Pin Name	I/O	Fuction	
1	GND	–		Ground
2	TxD	O	RS-232C	Transmission output
3	RxD	I	RS-232C	Receiving input
4	DTR	O	RS-232C	Transmission permission
5	POWER	I		Power control from the external
6	SW1	I	External option switch	∗1
7	SW2	I	External option switch	∗1
8	SW3	I	External option switch	∗1
9	SW4	I	External option switch	∗1
10	SW5	I	External option switch	∗1
11	SW6	I	External option switch	∗1
12	SW7	I	External option switch	∗1
13	SW8	I	External option switch	∗1
14	DLTST	I	For service	Down load pin (RS-232C level)
15	V+8	O	Not used	8V output

∗1: The player can be controlled by putting a switch on the outside of this terminal.
(The external option switch).

2. Specification of the external option switch terminal (D-SUB pins 6 to 13)
Input is pulled-up with 20 kΩ in +5V.
The player can be controlled by connecting a switch between this terminal and GND (D-SUB pin 1).



3. Power supply control from the external
In the POWER standby condition, perform the power ON processing when L signal is detected after H signal more than 100 msec.
In the power OFF condition, perform the power off processing and set it to the standby condition when the same signal is received.
Terminal voltage is ±12V, make H signal level is more than 4.5V, and L signal level is less than 0.5V.



■ Remote control unit



SPECIFICATIONS

General

System ..... DVD system and Compact Disc digital audio system
Laser ..... Semiconductor laser: wavelength 635 nm
Power requirements: ..... AC 120 V, 60 Hz
Power consumption ..... 23 W
Weight ..... 4.7 kg (10 lb 6 oz)
Dimensions ..... 210 (W) x 408 (D) x 119 (H) mm ($8\ ^{1}/_{4}$ x $10\ ^{1}/_{16}$ x $4\ ^{11}/_{16}$ in.) (Not including protruding cables, etc.)
Operating temperature ..... +5°C to +35°C (+36°F to +96°F)
Operating humidity ..... No more than 85% (no condensation)

S-Video Output

Y (luminance) - Output level ..... 1 Vp-p (75Ω)
C (color) - Output level ..... 286 mVp-p (75Ω)
Jacks ..... S-VIDEO jack

Video Output

Output level ..... 1 Vp-p (75Ω when loaded, synchronous negative)
Jacks ..... RCA

External synchronizing input

Input signal level ..... Black burst ..... 0.3 Vp-p (with 75Ω load) BNC x 2 (loop through)

Audio Output

Output level
During audio output ..... 200 mVrms (1 kHz, –20 dB)
Number of channels 2
Jacks ..... RCA

Digital audio characteristics

Frequency response	4 Hz to 22 kHz (DVD fs: 48 kHz) 4 Hz to 20 kHz (CD)
S/N ratio	115 dB (EIAJ) (typical)
Dynamic range	97 dB (EIAJ) (typical)
Total harmonic distortion	0.003 %
Wow and flutter	±0.001% W. PEAK or lower (EIAJ)

Other Terminals

Coaxial digital output (PCM/ ▯▯) ..... RCA jack
Communication interface ..... D-SUB, 15-pin

Accessories

Remote control unit 1
AA (R6P) dry cell batteries 2
Audio cord 1
Video cord 1
Laser bar-code Sheet 1
RF adaptor set clamp 1
Screw 1
Operating Instructions (Basic Operations) 1
Operating Instructions (Applied Operations) 1
Warranty card 1

NOTES:

All values listed in these specifications are standard values.

- *The specifications and design of this product are subject to change*
- *without notice, due to improvement.*

Accessories

Audio cord
(VDE1033) (L=1.5m)



Video cord
(VDE1048) (L=1.5 m)



Remote control unit
(VXX2553)



Dry cell batteries....2
(VEM-013)



Other included items:

- **Warranty card**
- **Operating linstructions**

PIONEER®
The Art of Entertainment

Service Manual

SERVICE GUIDE

ORDER NO.
RRV1896

DVD PLAYER
DV-505
DV-S9

DVD LD PLAYER
DVL-909

CONTENTS

PIONEER ELECTRONIC CORPORATION 4-1, Meguro 1-Chome, Meguro-ku, Tokyo 153-8654, Japan
PIONEER ELECTRONICS SERVICE, INC. P.O. Box 1760, Long Beach, CA 90801-1760, U.S.A.
PIONEER ELECTRONIC (EUROPE) N.V. Haven 1087, Keetberglaan 1, 9120 Melsele, Belgium
PIONEER ELECTRONICS ASIACENTRE PTE. LTD. 501 Orchard Road, #10-00 Lane Crawford Place, Singapore 0923

T - IZM APR. 1998 Printed in Japan

1. CIRCUIT DESCRIPTION

1.1 OVERALL BLOCK DIAGRAM

DV-505



DV-S9 and DV-09



DVL-909


IC601
PD3381A
System CPU
(32bit RISC)
4Mbit DRAM
VBR Buffer
IC702
HM514800CJ-7
IC701
PD4833A
LSI-11
IC603
FLASH ROM
IC602
GUI ROM
IC604
RAM
DRAM I/F
(Bus Arbiter)
Sync Demod
CPU I/F
ECC & ID Reg.
Spindle Control
CD-ROM Sync gene Sub-code Buffer
DMA
Sub-CPU I/F
Program Stream
27M
CD PCM
CD Digital out
16M
SPDL Motor
TA FA
Slider
For CLD
For DVD
HA OEIC
A/D
TE GEN
CD DSP
IC 201
LC78650E-P
EFM Decoder
Servo DSP
IC 501
PD4889A
Mechanism Control CPU
IC 813
CY2081SL-611
36M
SLD POS
XRESET
SI, SO, SCK, SHAKE
4
18M
Mecha. SW
DVD TILT ERR
LOAD/TILT MOTOR
TURN MOTOR
SLD DRV
SLD ERR
LOAD/TILT DRV
TURN DRV
IC101
PD0260A2
LD Mechanism Control
IC205
TC7S02F
X312
384 × 48k
(18M)
LD TILT ERR
Sel
TILT ERR
TRKG
FOCS
VCXO ERR
IC901
LA9430M
Servo Control IC (ASP)
IC801
LA9425
PSP
IC908
LC78625E
DSP
EFM Decode
LD DATA
56
IC352
CA0002AM
Analog Audio
25
4
15
14
Analog L
Analog R
Phillips Code
ACOM
IC400
LA7134M
VDEM
27
10
37
IC500
PD6159B
Dual DVP
SPDL Cont
14-21
65-72
44-51
IC101
PD3212A
Memory Cont. (with DNR)
IC102, IC103
MB81C1501PF
Field Memory
14M VCXO


IC802
MB811171622A
-100FN
16Mbit SDRAM
CODE Buffer
(Video, Audio, Sub-picture,GUI)
IC 801
MB86371
Memory Controller
CPU
I/F
System
Decoder
(DMUX)
MPEG 2
Video
Decoder
Sub
Picture
Decoder
GUI
MIX
NTSC
/PAL
Encode
Copy Gurd
DAC
DAC
DAC
AV Sync
Controller
AC3/MPEG1
Audio Decoder
S/PDIF
DVD/V-CD
AV Decoder
27M
36M
DVD Y
(IC815 ①)
Sync Tip
Clamp
(from MECHA. CONT. ㊶)
D-EXT ON/OFF
LD Y SIGNAL
(from MYCB)
AMP
D-Extention
Circuit
Pedestal
Clamp
Sync Tip
Clamp
LD Y
TRAP
IC620
Y OUT
C OUT
to
MYCB
BLANKING PLUSE
(from AV-1 ㊽)
BURST FLAG
(from AV-1 ㊼)
LD C SIGNAL
(from MYCB)
DVD C
(IC815 ⑦)
IC620
KEY
Front Section
FL
Cont.
FL TUBE
A.B.
Key
REMOTE
SENSOR
DATA
Hi-Bit
PCM Digital
PD
Key
DVD C.
DVD Y.
AC-3/PCM Digital
SEL IR
IR
X311
384 × 44.1k
(16M)
VCXO
Sel
IC203
TC74HC157AF
CLK
Hi-Bit
IC202
PD0236AM
D/A
L
R
Sel
Sel
IC201
PD2029AM (L)
16M
SR IN
SR OUT
L OUT
R OUT
JCKB ASSY
(COAXIAL)
(TOSLINK)
AC-3
/PCM
Digital
OUT
PCM
Digital OUT
AC-3 RF
AC-3 RF OUT
C (DVD)
Y (DVD)
IC301
CXD2046Q
Y/C SEP.
D/A
D/A
Y (LD)
C (LD)
1-8
IC620
IC620
TC74HC4053AF
Y OUT
C OUT
Comp. OUT
MYCB ASSY
CLDM ASSY

1.2 EXPLANATION OF EACH MOVEMENT

1.2.1 Sequence Up to Playback



1.2.2 Focus Servo

FE generated in the RF IC is sent to the Digital servo IC.
For a DVD, the servo is turned on during the transition from "Up" to "Down" of the first-order sine wave. For a CD, it turns on during the transition from "Down" to "Up" of the first-order sine wave.
When the servo is turned on, the level of PH (the envelope of the bright side of RF) increases, and DRF becomes H. The kick-brake pulses, such as those for FOCUS jump, are also output from pin 49 of IC201.

• FOCUS SERVO



• FOCUS LOCK TIMING



1.2.3 Tracking / Slider Servo

ATB: The tracking balance compensation is achieved by outputting the offset from the TBAL output at pin 46 of the digital servo IC, and by biasing the charge pump resistor for phase-difference error of RFIC.
The difference is detected by processing TE at pin 34 of IC 201 with an internal digital equalizer.

TDO: In addition to the servo output, the low-band components, such as the kick-brake for jump, are added for TDO output.

SLDO: The low-band components of TE are processed by the internal digital equalizer, and deadband is added for SLDO output. The offset voltage for pickup movement is also included in the SLDO output.

• TRACKING / SLIDER SERVO



1.2.4 SPINDLE SERVO

• SPDL SERVO



For a CD, the RF signal output from pin 32 of the RF IC is converted to binary in IC201. By comparing the binary value with the reference CLK (clock), the SPDL ERR signal is output from pin 48.
For a DVD, the SPDL ERR signal is generated from the PWM signal output from LSI-II. Upon receiving this signal via pin 31, IC201 also outputs it from pin 48, switching from the CD SPDL ERR signal.

1.2.5 Disc Determination

Determination is achieved by checking the sine wave by sweeping the lens with the OE IC gain at L and the FSC error amplifier (SGC) at the default setting. If no sine wave is detected, checking is retried after switching the OE IC gain to H and increasing the gain of the FSC error amplifier (SGC). If no sine wave is detected again, it is regarded as the NO DISC condition.
If one half of the sine wave detected at the first lens sweep is of a value less than 0.5 V, the OE IC gain is set to H and the peak-to-peak value of the sine wave is roughly adjusted to 1.8 Vp-p.
By sweeping the lens around the height where the sine wave has been detected, disc determination is performed, and the sine wave is finely adjusted to 1.8 Vp-p.



1.2.6 System Control (DVL-909)



1) Interface between Mode Cont. and System Cont.





Timing Chart

If there is no communication for 2 sec.,
Mode Cont. turn off the power and reset.

2. CIRCUIT DESCRIPTIONS FOR DV-S9 AND DV-09

2.1 VIDEO SIGNAL PROCESSING BLOCK

2.1.1 PD0259A Block

The major purposes of the PD0259A block are;
(1) Frame-correlative cyclic digital noise reduction
(2) Horizontal and vertical contour compensation
(3) Y/C timing adjustment
(4) Frame freezing

(1) Frame-Correlative Cyclic Digital Noise Reduction

For eight-bit digital video data input to the PD0259A, noise reduction is performed through subtraction between the data and those of the corresponding points 1 frame before, delayed for the subtraction via a 4-bit DRAM by 1 frame.
The noise signal detected as a result is sent to a non-linear circuit. If the difference is larger than a specific value, it is regarded as "a change in picture," and no canceling calculation is made.
This function is the same as that which has been performed in conventional laser-disc players. The only difference is that the input video signal here is a DVD digital component signal (4:2:2), while it is an LD digital composite signal in conventional laser-disc players.



(2) Horizontal and Vertical Contour Compensations

For data after digital noise reduction, horizontal and vertical contour compensations are made only for the Y-signal.
Horizontal compensation is performed by detecting edge components from the information of the reference picture elements and those that horizontally proceed and succeed by several pixels, and then generating edge-emphasizing components through non-linear processing of the detected components.
Vertical compensation is performed by detecting edge components from information on the reference picture elements and those which vertically proceed and succeed by one line, and then generating edge-emphasizing components through non-linear processing of the detected components.
These edge-emphasizing components are added to the main-line digital data to achieve contour compensations.



(3) Y/C-timing Adjustment

This function changes the output phase of the Y signal with respect to the Cb and Cr signals in units of the 13.5-MHz clock cycle (approx. 74 ns).

(4) Frame Freezing

In response to a command sent from the system control computer by serial transmission, data for one frame are frozen, and the frozen picture is output.
This function is specific to the DV-S9 and is used only for picture-by-picture reversing by jog/shuttle operation or "Slow 1" playback operation.

2.1.2 M65677FP Block

The M65677FP block functions as an NTSC encoder that converts digital component signals to analog Y, C, Cb and Cr signals. While our popular models other than the DV-S9 use the built-in encoder in the MB86371 block, an external NTSC encoder is added to the DV-S9, as it performs digital processing in the PD0259A block.

In addition to NTSC encoding, the M65677FP also performs:
(1) D.EXT(DV-S9)/BLACK LVL(DV-09)
(2) C.LEVEL adjustment

(1) D.EXT(DV-S9)/BLACK LVL(DV-09)

Setup of –7.5 IRE is added to the Y signal. D.EXT(DV-S9)/BLACK LVL(DV-09) processing using analog signals in conventional laser disc players is achieved by using digital signals.

(2) C.LEVEL Adjustments

The burst level of the C signal can be varied centering around 40 IRE.
Therefore, it is performed for the S-connector and CVBS-connector outputs, but not for the color-difference output.
This function is also not available if the connected TV receiver has no AGC circuit.

2.1.3 Analog Video Signal Processing Block

The video signals output from the built-in 10-bit DA converter of the M65677FP pass through a low-pass filter and amplifier, and are output from the DVD MAIN Assy and sent to the VOUT Assy.
In the VOUT Assy, analog noise-reduction processing having three levels (OFF, low, and high) is initially applied only to the Y signal. This analog noise reduction is the same as that performed by conventional laser-disc players. The register port output in serial communication that the PD0259A receives from the system-control computer is used as the control signal for analog noise reduction.
After analog noise reduction, a CVBS signal is generated by composing the Y and C signals (no clamping is performed for the C signal). The timing pulse BF to be used for pedestal clamping is supplied from the PD0259A. This signal is adjusted within the PD0259A so that it provides the timing for the burst portions of the output video signals.



2.2 DIRB BLOCK (DIRB ASSY) (DV-S9 ONLY)

The two major purposes of the DIRB block are the following:
(1) Switching between data reproduced from a disc and a data signal in DAC mode
(2) Data decoding in external input mode (DAC mode)

(1) Switching Between Data Reproduced from a Disc and a Data Signal in DAC Mode

The signal switching is performed at IC811, sending 3-line data (LRCK, BCK and DATA) to the AUDIO Assy. The switching control line (DAC MODE) is supplied from the DVD MAIN Assy. The master clock (MCK) is generated by a crystal on the AUDIO Assy when reproducing a disc, and by IC861 in DAC mode. MCK is sent to the AUDIO Assy via RXP.

(2) Data Decoding in External Input Mode (DAC Mode)

When the user selects DAC mode, the DAC MODE port is set to H and VCO in IC861 starts oscillating. (VCO does not oscillate in any other modes than DAC mode.) When there is a toss link of an external input or a coaxial digital input, the digital input signal is sent to IC861 from RXP of CN801, generating 3-line data corresponding to the input sampling frequency. At the same time, the master clock (MCK) to be used in DAC mode is also generated. For a 96kHz input, the MCK frequency is divided by 2 by IC831.

When the user selects the internal clock as the system clock, the clock generated by the crystal on the AUDIO Assy is sent to the DVD MAIN Assy. When the user selects an external sync as the system clock, the following parameters are used.

FS(kHz)	16M clock in the AUDIO Assy	18M clock in the AUDIO Assy	16M clock sent to the DVD MAIN Assy	18M clock sent to the DVD MAIN Assy
32	Oscillates	Oscillates	Crystal 16M clock	Crystal 18M clock
44.1	Stops oscillating	Oscillates	DIR 16M clock	Crystal 18M clock
48	Oscillates	Stops oscillating	Crystal 16M clock	DIR 18M clock
96	Oscillates	Stops oscillating	Crystal 16M clock	DIR 18M clock

If there is no external input or locking onto the input digital signal cannot be achieved, the ERR signal at pin 43 of IC861 is set to H, and the crystal in the AUDIO Assy immediately starts oscillating. In such cases, the clock sent to the DVD MAIN Assy will always be a crystal clock.



2.3 96K, 24-Bit, HIBIT LEGATO S SYSTEM (AUDIO ASSY)

All 16-bit and 20-bit sources are converted to 24-bit data by IC101, which lets a 24-bit data pass through.
As PCM1702P is a 20-bit D/A converter, processing of the upper 20 bits is assigned to it by the shift register.
The lower 4 bits are converted from serial to parallel, then the significance of each bit is converted digital to analog, functioning as a 4-bit D/A converter for the lower 4 bits.
By adding the lower 4 bits to the upper 20 bits in the low-pass & ADD block, D/A conversion is achieved for 24 bits.



3. TEST MODE

3.1 HOW TO ENTER THE TEST MODE

There is the three following methods in an enters of the test mode.
1. Short-circuit the terminals (TP6006 and TP6007) for test mode entry at the side of the system control IC (IC601) of DVDM ASSY, and turn the power on.
2. Input [ESC] key and [TEST/RANDOM] key of the test mode remote control unit in order under the power on condition.
3. Connect a personal computer with the RS232C terminal (CN106), and input entry command (TE) of test mode from the personal computer.

Note: FL indication and LED come all to light until key operation is done when entering the test mode.

3.2 RELEASE THE TEST MODE

There is the three following methods in a release of the test mode.
1. Turn the power off.
2. Press [ESC] key of the remote control unit. At this time, reset it for a while except for during the LD and CDV set.
3. Connect a personal computer with the RS232C terminal (CN106), and input normal mode entry command (NE) from the personal computer.

3.3 THE EXPLANATION OF EACH FUNCTION

The function that can be operated in the test mode is as the following. Use a LD remote control unit in the test mode.

(1) Door Open/Close

1. Press [REPEAT A-B] (48) key of the remote control unit.
2. Press [OPEN/CLOSE] key of the player from the stop condition.

(2) Stop

1. Press [REPEAT] (44) key of the remote control unit.
2. Press [STOP] key of the remote control unit or the player from the stop condition.

(3) Play 1 (Demultiplex exist which it tries to output the playback screen)

1. Press [PLAY] (17) key of the remote control unit.
   - CLD rise up at the tracking open condition. However, it becomes tracking close when entering the test mode during the play.
   - DVD rise up at the tracking close. Playback screen may not appear because the NAVI information isn't read in the test mode.

(4) Play 2 (Demultiplex is absent which performing trace only)

1. Press [TV/LDP] (0F) key of the remote control unit.
   - It is equal to the play 1 with CLD.
   - Perform only tracing with DVD, and there are no video and audio output.

(5) Pause

1. It becomes pause condition by pressing [CX] (0E) key of the remote control unit in the play.
2. Pause ON/OFF changes alternately by pressing [PAUSE] (18) key in the play.

(6) Search Address Input Entry

It becomes the address input mode when [+10] key (1F) is pressed. (indication for the most significant digit : >)
Indicate the last address as the initial condition in this time.
Only in case of DVD, addition search (indication for the most significant digit : +) and subtraction search (indication for the most significant digit : –) are able to select in order by pressing [+10] key continuously.
The address where input value was added to the present address is make to search with addition search.
The address where input value was subtracted to the present address is make to search with subtraction search.
In case of CD is only absolute time search.
Also address clear and release from the address input mode are able to perform by 2 steps by pressing [CLEAR] (45) key.

(7) Search Address Input

Press [0] to [9] keys of the remote control unit.
Set up the address by the hexadecimal number with DVD.
When [PROGRAM] (4C) key is pressed in the address input mode, input mode changes to hexadecimal number input (Indicates "*" mark), and [1] to [6] keys are input as [A] to [F].
At this time, [7], [8], [9] and [0] keys are not accepted.
Also the hexadecimal number input and the decimal number input can be changed with toggle.

(8) Search Practice

1. Press [CHP/TIM] (13) key of the remote control unit.
   Practice the on screen no playback (Doesn't demultiplex) after the search with DVD.
2. Press [PLAY] (17) key of the remote control unit.
   Practice the on screen playback (demultiplex exists) after the search with DVD.

(9) Side Change

This function becomes effective when a set disk is LD.
1. Change a side on the side A from the side B when pressing [SIDE A] (4D) key of the remote control unit.
2. Change a side on the side B from the side A when pressing [SIDE B] (4E) key of the remote control unit

(10) Tracking Open

1. Press [STEP FWD] (54) key of the remote control unit in the play condition.
2. Switch the open/close by pressing [PLAY] key of the remote control unit or the player during the play (CD only).

(11) Tracking Close

1. Press [STEP RVS] (50) key of the remote control unit in the play condition.
2. Switch the open/close by pressing [PLAY] key of the remote control unit or the player during the play (CD only).

(12) Slider In

1. Press [SCAN RVS] (11) key of the remote control unit in the tracking off condition.
2. Turn the shuttle of the remote control unit in the REV direction (2C to 2F) in the tracking off condition. (DVD only)

(13) Slider Out

1. Press [SCAN FWD] (10) key of the remote control unit in the tracking off condition.
2. Turn the shuttle of the remote control unit in the FWD direction (28 to 2A) in the tracking off condition. (DVD only)

(14) Scan In

1. Press [SCAN RVS] (11) key of the remote control unit in the tracking on condition.
2. Turn the shuttle of the remote control unit in the REV direction (2C to 2F) in the tracking on condition.
   - DVD can be scanned only in the case of the play 2 (playback without demultiplex).

(15) Scan Out

1. Press [SCAN FWD] (10) key of the remote control unit in the tracking on condition.
2. Turn the shuttle of the remote control unit in the FWD direction (28 to 2A) in the tracking on condition.
   - DVD can be scanned only in the case of the play 2 (playback without demultiplex).

(16) Loading In/Out

When pressing [SKIP REV] (53) key of the remote control unit in the open condition, it loads in the clamp direction. Then it loads in the open direction when pressing [SKIP FWD] (52) key.

- This function can practice only when it is indicated with "OPEN" in FL.

(17) Tilt Neutral

Press [SPEED DOWN] (46) key of the remote control unit.

(18) Tilt Servo On/Off

a. On
Press [SPEED UP] (47) key of the remote control unit.

b. Off
Press [SKIP REV] (53) key and [SKIP FWD] (52) key of the remote control unit at the tilt servo on or the tilt neutral.

(19) Tilt Down

A manual moves in the going down direction when [SKIP REV] (53) key of the remote control unit is pressed during the play at the time of tilt off.

(20) Tilt Up

A manual moves in the going up direction when [SKIP FWD] (52) key of the remote control unit is pressed during the play at the time of tilt off.

(21) Focus Jump +

Focus jumps in 1 layer from 0 layer when [MULTI FWD] (58) key of the remote control unit is pressed. (DVD only)

(22) Focus Jump –

Focus jumps in 0 layer from 1 layer when [MULTI REV] (55) key of the remote control unit is pressed. (DVD only)

(23) The First And The Second Screen Switching

Every time [DISPLAY] (43) key of the remote control unit is pressed, the contents of the version indication part (the bottom right of the screen) change. (Refer to page 17.)

(24) Screen Display On

1. Press [DISPLAY] (43) key of the remote control unit.
2. Display on/off switches every time [PROGRAM] (4C) key of the remote control unit is pressed.
   - When [DISPLAY] key is pressed in the display on, change the part number indication of the microprocessor and revision indication.
   - Initial state is screen display on and it becomes the part number indication of the microprocessor.

(25) Screen Display Off

1. Press [AUDIO] (1E) key of the remote control unit.
2. Display on/off switches every time [PROGRAM] (4C) key of the remote control unit is pressed.

(26) Background Color Switching

1. Change the background color (eight colors) prepared for in advance every time [2/R] (49) key of the remote control unit is pressed in order.
   [Blue→Green→Light blue→Red→Purple→Yellow→ Gray→Black→Blue ....]
2. Change the background color (eight colors) prepared for in advance every time [1/L] (4B) key of the remote control unit is pressed in order.
   [Blue→Black→Gray→Yellow→Purple→Red→ Light blue→Green→Blue ....]

(27) Video Output Switching

1. It becomes component output when pressing [DIGITAL EFFECT] (5C) key of the remote control unit.
2. It becomes composite output when pressing [STILL WITH SOUND] (5B) key of the remote control unit.

3.4 EXPANSION FUNCTION 1

Set the reception mode of expansion function by pressing [TEST] (5E) key of the test mode remote control unit, then expansion function is able to execute by pressing the key of [0] to [9].
Indication for the most significant digit becomes "T" during the reception mode of expansion function. (This mode can on and off with toggle.)

(1) LD On

Turn the laser diode to on by pressing [TEST] and [1] keys in order.

(2) Focus On

Focus locks by pressing [TEST] and [2] keys in order.

(3) Focus Sweep

Repeat focus sweep by pressing [TEST] and [3] keys in order.

(4) Spindle FG Servo

Rising up the spindle and FG servo becomes on by pressing [TEST] and [5] keys in order.

(5) AGC On/Off

Switch the AGC on and off with toggle by pressing [TEST] and [7] keys in order.

(6) Jitter Value Indication.

It becomes the jitter-value indication mode by pressing [TEST] and [DIG/ANA] keys in order.

(7) DSP coefficient indication of FTS system.

Set up the address (four digits) of the coefficient that it wants to see by the point of search address input, then real time indicates the coefficient in OSD by pressing [TEST] and [9] keys in order.

(8) CD Error Rate Indication

Indicate the value in OSD after measuring is completed by pressing [TEST] and [0] keys in order after set up the measuring time (1 to 8 seconds) by the point of search address input.

3.5 EXPANSION FUNCTION 2

Set the reception mode of expansion function 2 by pressing [HILITE/INTRO] (55) key of the remote control unit, then expansion function 2 is able to execute by pressing the key of [0] to [9].

(1) Forced DVD Setting

In the checker mode, set up the condition that DVD is attached forcibly except for the result of disc distinction by pressing [HILITE/INTRO] and [1] keys in order.
In the no checker mode (normal test mode), once execute the setting but abandan it soon.
Therefore, perform the disc distinction again for the safety when rising up the player in this condition.

(2) Forced CD Setting

In the checker mode, set up the condition that CD is attached forcibly except for the result of disc distinction by pressing [HILITE/INTRO] and [3] keys in order.
In the no checker mode (normal test mode), once execute the setting but abandan it soon.
Therefore, perform the disc distinction again for the safety when rising up the player in this condition.

(3) Execute The Disk Distinction

In the checker mode, execute the disc distinction result by pressing [HILITE/INTRO] and [0] keys in order.

3.6 List of Test Mode Function

Contents of Command	Condition	Key Name of Remote Control Unit	Mode of Remote Control Unit
Open	STOP	REPEAT A	A8-48
Close	OPEN	REPEAT A	A8-48
Stop	PLAY	REPEAT B	A8-44
Play (DVD is only tracing.)	STOP	TV/LDP	A8-0F
Play (DVD is with decode.)	STOP	PLAY	A8-17
Pause on	PLAY	CX	A8-0E
Pause on/off	PLAY/PAUSE	PAUSE	A8-18
Search address input (0 to 9) ∗Use for other numerical value input		0 to 9	A8-00 to 09

Contents of Command	Condition	Key Name of Remote Control Unit	Mode of Remote Control Unit
Search address input (A to F)	During address input	PGM+1 to 6	
①Search address clear ②Escape the search input mode	During address input Address = 0	CLEAR	A8-45
Change the search address input mode (Off→absolute address→addition→subtraction→Off) ∗Use for other numerical value input.		+10	A8-1F
Search execution (ignore the wrong address)		CHAP/TIME	A8-13
Side change (side B→side A)	LD	SIDE A	A8-4D
Side change (side A→side B)	LD	SIDE B	A8-4E
Tracking open	PLAY	STEP FWD	A8-54
Tracking close	PLAY	STEP REV	A8-50
Slider in	TR : Off	SCAN REV Shuttle REV	A8-11 A8-2C to 2F
Low speed scan REV	TR : On	SCAN REV	A8-11
Scan REV (Jump number is variable)	TR : On	Shuttle REV	A8-2C to 2F
Slider out	TR : Off	SCAN FWD Shuttle FWD	A8-10 A8-28 to 2B
Low speed scan FWD	TR : On	SCAN FWD	A8-10
Scan FWD (Jump number is variable)	TR : On	Shuttle FWD	A8-28 to 2B
Loading in	STOP	SKIP REV	A8-53
Loading out	STOP	SKIP FWD	A8-52
Tilt neutral		SPEED DOWN	A8-46
Tilt servo on		SPEED UP	A8-47
Tilt servo off	Tilt : On/N	SKIP REV SKIP FWD	A8-53 A8-52
Tilt up	PLAY	SKIP FWD	A8-52
Tilt down	PLAY	SKIP REV	A8-53
LD on		TEST + 1	A8-5E + A8-01
Focus on		TEST + 2	A8-5E + A8-02
Focus sweep		TEST + 3	A8-5E + A8-03
Focus jump +		MULTI FWD	A8-58
Focus jump –		MULTI REV	A8-55
Spindle FG on		TEST + 5	A8-5E + A8-05
AGC on/off	AGC : Off/On	TEST + 7	A8-5E + A8-07
Indication of the FTS coefficient	After the address four-digit input	TEST + 9	A8-5E + A8-09
CD error rate indication	PLAY	TEST + 0	A8-5E + A8-00
Jitter indication		TEST + DIG/ANA	A8-5E + A8-0C
Screen indication on/Switching of the first screen and second screen	OSD Off/On	DISPLAY	A8-43
Screen indication off	OSD : On	AUDIO	A8-1E
Screen indication on/off		PROGRAM	A8-4C
Switching of ID display methods (decimal/hexadecimal)		DIG/ANA	A8-0C
DISC type designation • Forced designation to DVD • Forced designation to CD • Request for Disk sensing	STOP	HILITE/INTRO +1 +3 +0	A8-5A +A8-01 +A8-03 +A8-00
Tray close of disk sense inhibition	Checker mode	REPEAT A	A8-48
Background color (eight colors) switching Background color (eight colors) switching (reverse toggle)		2/R 1/L	A8-49 A8-4B
Video : component output		DIGITAL EFFECT	A8-5C
Video : composite output		STILL WITH SOUND	A8-5B

● Special Mention Item

(1) Indications for the spindle status are as follows:
A/B : Spindle accelerator and brake
FG : FG servo
SRV : Rough, velocity/phase servo
O_S : Offset addition, rough, velocity/phase servo

(2) The movement of loading in/out starts from the tray open status. After that, this function is executed unless a play and close operation are done.

(3) There are three methods for entering a search address:
① Absolute address designation
→ Searching for the address entered (indication for the most significant digit :>)
② Additional input
→ Searching for the address with the current ID number plus an entered number
(indication for the most significant digit :+)
③ Subtractive input
→ Searching for the address with the current ID number minus an entered number(indication for the most significant digit :–)
The above modes can be changed by pressing [10] key.
Note : A number for addition or subtraction must be entered in hexadecimal.

(4) If you turn the power on while short-circuiting the short-circuit terminal at the side of the system controller, the player will forcibly enter the test mode. If the FL controller is set to Checker mode, disc sensing will not be started, even if a disc is loaded. Disc sensing will also not be performed if the tray is opend/closed by your pressing [REPEAT A] key while in Checker mode.
However, disc sensing will be started if the [OPEN/CLOSE] key on the player or on the remote control unit is pressed.

(5) If disc-type designation is forcibly executed during a mode other than Checker mode, the system controller will abandon disc-type designation after setting the mechanism controller. Therefore, after startup of the player, disc sensing will be performed again for safety.
If disc-type designation is forcibly executed during Checker mode, as disc-type designation is not abandoned, playback will be immediately started.

(6) A background color change in order of blue → green → light blue → red → purple → yellow → gray → black → with the [2/R] key.
It changes in order of gray → yellow → purple → red → light blue → green → blue → black → in the case of the [1/L] key.

(7) In case of PD0260A∗, tilt servo on function may not move with DVD.

3.7 Test Mode Screen Display (The Second Generation)

Consecutive double-OSD display is supported during test mode. The screen is composed 10 lines with a maximum of 32 characters per line. It can't be used with the debugging display mode together.

• Screen Composition



First screen display

Caution :
The first screen and second screen switch by pressing [DISPLAY] key of the remote control unit.
It is only a version display part on the lower right of the screen those contents of display change.
ATB : ON/OFF information display and AGC manual establishment display deleted with the second generation.



Second screen display (at lower right portion of the screen)

• Description of Each Item on the Display

(1) Address indication

The address being traced is displayed in number.

DVD	: ID indication (hexadecimal number, 8 digits)	[＊＊＊＊＊＊＊＊]
CD/LD (CLV)	: A-TIME (min. sec.)	[○○○○＊＊＊＊]
LD (CAV)	: FRAME	[○○○＊＊＊＊＊]

(Note : For DVDs, decimal-number indication is possible.)

(2) Code indication of the remote control unit [R-＊＊＊＊]

The code for the key pressed on the remote control unit, which is received by the FL controller, is displayed while the key is pressed. In the case of the double code, the second code will be displayed.

(3) Key code indication for the main unit [K-＊＊]

The code for the key pressed on the main unit, which is received by the system controller, is displayed while the key is pressed.

(4) Tilt error value, Tilt servo status [TILT-＊:＊＊＊]

Tilt error value :	[0] to [F]
Tilt servo status :	
Tilt neutral	[N]
Tilt servo on	[ON]
Tilt servo off	[OFF]

(5) Tracking status [TRKG-＊＊＊]

Tracking on	[ON]
Tracking off	[OFF]

(6) Spindle status [SPDL-＊＊＊]

Spindle accelerator and brake	[A/B]
FG servo	[FG]
Rough, velocity phase servo	[SRV]
Offset addition, rough, velocity phase servo	[O_S]

(7) Mechanism position value [M-＊]

Position code	[0] to [8]

(8) Slider position [S-＊＊＊＊]

CD TOC area	[IN]
CD active area	[CD]
CDV video area	[CDV]
LD active area	[LD]
Side B inside	[B IN]

(9) AGC setting [AGC-＊＊]

AGC on	[ON]
AGC off	[OFF]

(10) Output video system [V-＊＊＊＊]

NTSC system	[NTSC]
PAL system	[PAL]
Auto-setting	[AUTO]

(11) FTS servo IC information

Indications for the following two types of information can be switched:

① DSP coefficient indication [KS-[＊＊＊＊] ＊＊＊＊]
Displays the address (four digits) of the specified coefficient and the setting value (four digits) with [TEST] and [9] keys.

② Jitter value indication [JT-[○○○○]＊＊＊＊]
Displays the jitter value (four digits) with [TEST] and [DIG/ANA] keys.

(12) Error rate indication

① C1 error value of CD	[ER-C1 ＊＊＊＊]
② C1 error value of DVD	[ER-＊＊＊＊ ＊＊＊＊]

(13) Internal operation mode of mechanism controller [MM-＊＊:＊＊]

Internal mechanism mode (2 digits) and internal mechanism step (2 digits) of the mechanism controller
Note : For details, see the specifications of the mechanism controller.

(14) Disk sensing [DSC-＊＊＊]

The type of discs loaded is displayed.
[DVD], [CD], [CDV], [LD], [VCD], [ ]

(15) Pickup [PU-＊＊＊]

The pickup being operating is displayed.

DVD	[DVD]
CLD	[CLD]

(16) Destination setting of the FL controller [F:＊＊＊/＊＊＊]

Three characters in front represent the type of model:
505: DV-505, S9: DV-S9
606 : DV-606D, EDU: for education
909: DVL-909, K88: DVL-K88.

Three characters that follow represent the destination code.
J : /J, K: /KU, /KC, /KU/KC, RAM: /RAM (China)
RL : /RL, WY: /WY, RD: /RD.
＊ Furthermore DVL-91/KU/CA indicates as L91/K.

(17) Region setting of the player [REG:＊]

Setting value [1] to [6]

(18) Version of the flash ROM [V:＊.＊＊]

(19) Revision of the system controller [S:＊.＊＊＊/＊.＊＊]

① Revision number of the external ROM part (flash ROM) of the system controller <Front>
② Revision of the internal ROM part of the system controller <Rear>

(20) Revision of the DVD mechanism controller [M:∗.∗∗∗/∗.∗∗∗]

① Revision number of the external ROM part (flash ROM) of the DVD mechanism controller <Front>

② Revision of the internal ROM (core part) of the DVD mechanism controller <Rear>

(21) Revision of the CLD mechanism controller [L:∗.∗∗∗]

(22) Version of the AV-1 chip [AV:∗.∗]

(23) Version of the FL controller [F:∗.∗]

(24) Control number of the GUI-ROM [GUI:∗∗∗]

(25) The part number of the flash ROM and system controller [S : ∗∗∗∗∗∗/∗∗∗∗∗∗∗]

① Part number of the flash ROM <Front>
(Example) VYW1536-A → W1536A
(Example) PD626A9 → 6256A9

② Part number of the system controller <Rear>
(Example) PD3381T1 → 3381T1

(26) Part number of the DVD mechanism controller
(Example) PD4889A0 → 4889A0

(27) Part number of the CLD mechanism controller
(Example) PD0260A2 → 0260A2

(28) AV1 classification [AV1 : ∗∗∗]
RAM, E/A, S/C

(29) Flash ROM size [FLSH : ∗∗]
8M : 8M bit, 4M : 4M bit

3.8 DESCRIPTIONS OF NEW FUNCTIONS IN TEST MODE

3.8.1 Error Rate

● Overview

The error rate of CDs can be measured on basic models, such as the DV-505, and that of CDs as well as LDs with sub-Q codes can be measured on DVD/LD-compatible models, such as the DVL-909.
The value is displayed in decimal and indicates the number of C1 errors (including the corrected ones) counted during the specified measurement time.
An indeterminate measurement result may be caused by a dirty disc, decentering, surface deflection, birefringence (double reflection), or a pickup problem (dirty lens, etc.), misadjustments of the pickup, improper automatic adjustment, or incomplete adjustments. On the manufacturing line, the value is used for yes/no decision of pickups. Normally, for a measurement for 5 seconds, the value may be less than 10 with a clean disc and less than 100 with a disc with some damage.

● Using the Function in Test Mode (The Remote Control Keys to be Used are Indicated in Brackets)

(1) Set the CD to trace (playback) state.
(2) Set the player to Number input mode by pressing [+10] and enter the measurement time in a range of 1 to 5 (sec.).
(3) Start measurement by pressing [TEST] + [0]. The SubQ counter stops during measurement, but this is not a malfunction. When the specified measurement time has elapsed, the result is indicated to the right of "ER C1 –" on the screen.
If you skip step 2, the measurement time is set to 5 (sec).

3.8.2 Jitter Value

● Overview

The jitter values of DVDs and CDs can be displayed on basic models, such as the DV-505, and those of DVDs can be displayed on DVD/LD-compatible models, such as the DVL-909.
The displayed value shows a voltage in three-digit decimal as ○.○○ V. For example, the indication "0278" means 2.78 V. The larger the value, the worse the jitter. The worst value is 3.25 V. When playing a DVD or a video CD with which the jitter value is extremely high, mosaics may be seen. As with the error rate, the jitter depends on the disc and pickup. The jitter value to be displayed has no close correlation with a jitter measuring device, and is to be regarded just for reference.
Reference : When the jitter value is 2.9 V or more with a DVD, or 3.0 V or more with a CD (or a video CD), it may cause a problem (mosaic, audio distortion, etc.) in playback.

● Using the Function in Test Mode (The Remote Control Keys to be Used are Indicated in Brackets)

(1) Set the DVD or CD to trace (playback) state with AGC OFF.
(2) Press [TEST] and [DIGITAL/ANALOG].
The current jitter value appears to the right of "JT:○○○" on the display. The jitter value keeps changing unless any additional key operation is made.

Note : Although a value may be displayed on the screen even with AGC ON, this is NOT a jitter value.
The jitter value with AFB ON cannot be displayed (see the next section). The jitter value with AFB ON can be obtained only by directly measuring the voltage at the JV connector (pin 94) of the servo DSP (LC78650).

3.8.3 Startup Sequence

The basic flow is shown below. The parentheses indicate a limitation: "base" represents base models, such as the DV-505 and DV-S9, and "compatibles" represents DVD-LD compatible models, such as the DVL-909.

(1) Closes the tray.
(2) Runs the tilt servo for 1.5 seconds (compatibles).
(3) Detects the peak.
(4) Distinguishes the disc.
(5) SGC
(6) Turns on the focus servo.
(7) Turns on the tilt servo (compatibles).
(8) Starts the spindle rotation.
(9) ATB
(10) Measures the MIRR modulation degree.
(11) Turns on the tracking servo.
(12) Turns on the slider servo.
(13) Turns on the spindle servo.
(14) Focus AGC
(15) Tracking AGC
(16) AFB
(17) Plays AGC (base for CDs)
(18) Plays back.

* For a 2-layer DVD, steps (9) through (16) are repeated for each layer.
* When starting up with [TV/LDP] in Test mode, all the steps (1) to (18) are performed for a DVD, and steps (1) to (10) are performed for a CD.

3.8.4 Peak Detection

● Overview

This is a new function to measure the size and location of the sine wave related to focus errors at the beginning. The measurement is performed in the normal startup process and in Test mode, as well. If the sine wave is small, the OE IC gain is switched. Only the judgment for NO DISC is accomplished at this time. The operation is in effect as for judgment for DISC .

● Using the Function in Test Mode

This function is not assigned to any remote control keys. Only an open/close operation can trigger the function.

3.8.5 Disc Distinction

● Overview

This function is almost the same as that with the first-generation models. The only difference is as follows: If an error occurs in the startup sequence and playback cannot be started, startup is retried after forcibly switching the disc distinction from DVD to CD or vice verse by a backup process. If startup fails again, it is canceled, and an error is generated. The types of error that triggers the backup process for disc distinction are discussed in the next section.

● Using the Function in Test Mode

This function is not assigned to any remote control keys. Only an open/close operation can trigger the function.

3.8.6 SGC

● Overview

This is a new function to maintain the sine wave related to focus errors to a certain size so that the sine wave shows 1.8 V for the P-to-P value.
This operation is performed each time after judging disc presence and distinction in the normal startup process and in Test mode, as well. The operation is achieved by switching the FE gain inside the RF IC (LA9700) by using the voltage at the SGC connector (pin 22) of the RF IC.

● Using the Function in Test Mode

This function is not assigned to any remote control keys. Only an open/close operation can trigger the function.

3.8.7 Measurement of MIRR Modulation Degree

● Overview

The slice voltage of the RF signal is measured and used in the calculation to generate the MIRR signal. This operation is made in synchronization with ATB ON/OFF in normal startup and in Test mode, as well.

3.8.8 AFB (Auto Focus Bias) Function

● Overview

Among the first-generation models, this function supports only CDs with the basic models, such as the DV-7. Among the new models, this function supports DVDs with all models, but CDs only with the basic models. The operation is executed only once (once for each layer for a 2-layer DVD) after the focus and tracking AGC at startup. The operation is accomplished not by centering the focus servo to Vref (2.5 V), but by gradually changing the center value for the optimum jitter value. Thus, performance with an improper or dirty disc (by fingerprints, etc.), or the temperature characteristics (at 0°C, 35°C, etc.) will be improved.

● OverviewUsing the Function in Test mode (the Remote Control Keys to be Used are Indicated in Brackets)

As the function is to be synchronized with AGC, turn on and off AFB by pressing [TEST] + [7]. The jitter value measurement cannot be made with AFB ON.

3.8.9 PLAY AGC

● Overview

The SGC voltage is adjusted during playback according to the RF signal level. (For details on SGC, see section 3.8.6.)
Only for CDs in basic models, such as the DV-505 (including the DV-S9), this adjustment is made only once immediately after AFB during startup. In Test mode, it synchronizes with AGC ON/OFF. The operation is achieved through adjustment in the Servo DSP (LC78650), and the SGC voltage is output via AUX0 (pin 44).

● Using the Function in Test Mode (the Remote Control Keys to be Used are Indicated in Brackets)

As the function is to be synchronized with AGC, turn on and off AFB by pressing [TEST] + [7].

3.9 Additional Descriptions of Error Generation

This section describes the major errors of the mechanism-control computer.

(1) DISC Distinction Error (Error 38)

The most common error. The tracking overcurrent error (Error c3), Defocus error (Error 33), spindle errors (Errors 41 to 4b), auto sequence errors (Errors 51 to 55) and code misread errors (71 to 74) often lead to this error.

(2) Search Errors (Errors 11, 12, 19)

Almost all cases where playback suddenly stops may involve these errors. They may be generated because of defects on the disc, or if the pickup goes too far over the inner periphery with DVD/LD-compatible models. As with the code misread errors below, they can also be generated by a dirty disc or bad jitters.

(3) Code Misread Errors (Errors 71 to 74)

Almost all cases where the inserted disc does not start or immediately stops playing may involve these errors. They may be generated because of a dirty disc or bad jitters. A bad jitter may be caused by a dirty disc, decentering, surface deflection, birefringence (double reflection), or a pickup problem (dirty lens, etc.), misadjustments of the pickup, improper automatic adjustment, or incomplete adjustments.

(4) Spindle Errors (Errors 48, 49)

An FG transition timeout (Error 48) may be generated because of instability of the FG signal or unavailability of spindle drive voltage. A PLL transition timeout (Error 49) can be generated with a dirty disc.

(5) Automatic Sequence Errors (Errors 51 to 55)

If any automatic sequence (auto execution command) of the servo DSP is not completed, these errors are generated. The causes differ among error numbers. They may be caused by abnormalities in the communication line between the mechanism-control computer (PD4889A) and the servo DSP or instability of the XABUSY connector (pin 38) of the mechanism-control computer.

(6) DSP Communication Errors (Errors a1 to a6)

These errors will be generated if the mechanism-control computer cannot properly communicate with the servo DSP. They may be caused by instability of the XCBUSY connector (pin 8) of the mechanism-control computer, instability of the communication line between the mechanism-control computer and the servo DSP, or a defect in the servo DSP.

(7) DVD Block Noise, etc.

Block noise and momentary picture freeze (∗) with a DVD are not regarded as errors, but the causes of these symptoms in the Servo system may be:

(1) A search takes a long time (leading to a search error if it worsens).
(2) Codes cannot be read clearly (leading to a code misread error if it worsens).
If the value to the right in the "ER: ◯: ◯e–" indication displayed on the screen by pressing the ESC and DISP keys of the remote control in Test mode is greater than 5, the cause may be (1). If the value is less then 3, the cause may be (2).

(∗) With a specific 2-layer disc with which playback continues from layer 1 to 2 or vice versa, the picture may be seen momentarily stop. This may be attributed to the performance of the player. Players of other manufacturers have the same symptoms to varying degrees.

4. IC INFORMATION

• The information shown in the list is basic information and may not correspond exactly to that shown in the schematic diagrams.

● List of IC

PD4890A, PD0260A2, PD0261A2, LA9700M, BA6195FP, LC78650E-P, PD4889A, SRM2B256SLMX70, VYW1536, PD3381A, MB86371, MB811171622A-100FN, CY2081SL-611, PD2058A

■ PD4890A (FLKB ASSY : IC101)

• Mode Control IC

● Block Diagram



● Pin Function

No.	Mark	Pin Name	I/O	Function
1	P94	G7	O	FL timing output H : ON
2	P93	G6		
3	P92	G5		
4	P91	G4		
5	P90	G3		
6	P81	G2		
7	P80	G1		
8	VDD	VCC	–	Power supply pin
9	P27	(NC)	O	Not used
10	P26	(NC)		
11	P25	(NC)		
12	P24	LAMP	O	DVD lamp ON/OFF H : ON
13	P23	XREADY	O	Communication handshake line with the system controller L :Permit the communication
14	P22	SCK	I/O	Communication clock output with the system controller
15	P21	SO	I/O	Communication data output with the system controller
16	P20	SI	I	Communication data input with the system controller
17	RESET	RESET IN	I	Reset input L : reset
18	P74	(NC) (DV-505)	O	Not used
		SIDE A LED (DVL-909)	O	SIDE A LED ON/OFF L : ON
19	P73	(NC) (DV-505)	O	Not used
		SIDE B LED (DVL-909)	O	SIDE B LED ON/OFF L : ON
20	AVss	Vss	–	GND pin
21	P17	POWER ON	O	SW 5V ON/OFF H : ON
22	P16	RESET OUT	O	System reset output L : reset
23	P15	(NC)	O	Not used
24	P14	(NC)		
25	P13	KIN1	I	Key input
26	P12	KIN0		
27	P11	MS1	I	Destination judgement input
28	P10	MS0		
29	AVDD	AVDD	–	Power supply pin
30	AVREF	AVREF	–	Reference voltage
31	P04	P04	I	Not used
32	XT2	(NC)	–	Not used
33	VSS	VSS	–	GND pin
34	X1	X1	I	Connect a microprocessor clock
35	X2	X2	–	
36	P37	(NC)	O	Not used
37	P36	(NC)		
38	P35	(NC)		
39	P34	P34	I	Not used
40	P33	P33		

No.	Mark	Pin Name	I/O	Function
41	P32	P32	I	Not used
42	P31	P31		
43	P30	(NC)	I	Not used
44	P03	P03	I	Not used
45	P02	ON POWER	I	Switch the STBY/POWER ON at rising edge the FL controller L : STBY
46	P01	LT	I	Communication handshake line with the system controller H : Permit the communication
47	P00	SEL IR	I	Remote control signal input
48	IC	IC	–	–––
49	P72	(NC)	O	Not used
50	P71	FL OFF LED (DV-505)	O	FL OFF LED ON/OFF L : ON
		(NC) (DVL-909)	O	Not used
51	P70	(NC)	O	Not used
52	VDD	VDD	–	Power supply pin
53	P127	(NC) (DV-505)	O	Not used
		FL OFF LED (DVL-909)	O	FL OFF LED ON/OFF H : ON
54	P126	(NC)	O	Not used
55	P125	(NC)		
56	P124	(NC)		
57	P123	(NC)		
58	P122	(NC)		
59	P121	(NC)		
60	P120	(NC)		
61	P117	P15	O	FL segment output H : ON
62	P116	P14		
63	P115	P13		
64	P114	P12		
65	P113	P11		
66	P112	P10		
67	P111	P9		
68	P110	P8		
69	P107	P7		
70	P106	P6		
71	VLOAD	-27V	–	– 27V input H : ON
72	P105	P5	O	FL segment output H : ON
73	P104	P4		
74	P103	P3		
75	P102	P2		
76	P101	P1		
77	P100	G11	O	FL timing output H : ON
78	P97	G10		
79	P96	G9		
80	P95	G8		

■ PD0260A2, PD0261A2 (CLDM ASSY : IC101)(DVL-909 ONLY)

• Mechanism Control IC

● Pin Function

No.	Pin Name	I/O	Function
1	VCC	I	Power supply pin Apply 5V ± 10%
2	RWC	O	DSP read/write command signal output "L"= Read "H"= Write
3	XPLAY	O	Signal output during spindle servo "L"= During servo "H"= During acceleration, brake and stop
4	CLK:SCK3/CQCK	O	DVP/DSP clock switch "H"= DVP "L"= DSP
5	XCD	O	LD/CD switch signal output "L= CD "H"= LD
6	TILT ERR	I	A/D • This signal is A/D converted as the tilt servo control input. Control the tilt motor so that this signal becomes 2.5V.
7	TRK BAL ERR	I	A/D • Tracking balance error signal input This signal is A/D converted as the tracking offset control input.
8	SLD ERR	I	A/D • This signal is A/D converted as the slider servo control input. Control the slider motor so that this signal becomes 2.5V.
9	SLD POS	I	A/D • Pickup position detection switch input Detect the position by reading A/D input value which each switches are resistance divided.
10	FSEQ	I	Subcode sync. confirmity detection signal input "L"= Not confirmity "H"= Confirmity
11	C DETECT	I	Spindle over-current detection signal input "L" = Over current "H"= Normal
12	TRK BAL DRV	O	PWM • Output the tracking offset signal to PWM output, then use for auto tracking offset. 910 µsec period, tri-state control H, L, Z
13	SHAKE	I/O	Handshake signal for data communication with the DVD mechanism control IC This pin is the bilateral data line and each microprocessor control the Input/Output.
14	RF CORRECTION	O	RF correction switch signal output "H"= Gain UP CD, CDV-A:Low, CAV inner circuit gain up, others are High.
15	SQOUT	I	Command data input from DSP Read out SUBQ
16	SO3/COIN	O	Command data output to DVP/DSP
17	SCK3/CQCK	O	DVP/DSP read/write command clock output Read-in at rising edge
18	SLD OUT	O	PWM • Slider control signal output 5V= FWD, 0V= REV, 2.5V= STOP 910 µsec period, tri-state control
19	SI1	I	Data input from the DVD mechanism control IC
20	SO1	O	Serial data output to the DVD mechanism control IC
21	SCK	I/O	Clock for serial communication with the DVD mechanism control IC Becomes input mode without communicate with the DVD mechanism control IC
22	TRK 0 CRS	I	INT • Tracking error zero cross signal input Monitor this signal when searching track count in the miss clamp detection
23	SBSY	I	Subcode block sync. input
24	TILT OUT	I/O	LOAD/TILT control output PWM output 0V : Tray IN / Tilt DOWN, 5V : Tray OUT / Tilt UP, 2.5V : STOP
25	TURN OUT	O	Turn drive signal output
26	XPBV	I	Playback vertical sync. signal input of LD/CDV "L"= During vertical sync.
27	CNVSS	I	Ground for A/D conversion
28	XRESET	I	Reset signal input "L"= Reset "H"= Release reset Control with the DVD mechanism control IC.
29	XIN	I	9MHz clock oscillation input
30	XOUT	O	9MHz clock oscillation output

No.	Pin Name	I/O	Function
31	PHAI	O	Not used
32	GND	I	Ground
33	SW1	I	Switch input for Loading/Tilt position detection
34	SW3		
35	SW2		
36	TBCLOCK	I	Spindle lock signal input "L"= Unlock "H"= Lock
37	FG	I	Spindle motor FG signal input 16 outputs per rotation Used after dividing by 2 in the microprocessor
38	DATA	I	Input for Phillips code decoder with built-in mechanism controller
39	XPBH	I	Playback H-SYNC input for Phillips code decoder
40	XPBV	I	Playback V-SYNC input for Phillips code decoder
41	DEXT	O	Control signal output of video dynamic range extension "H"= ON "L"= OFF
42	WFM/VLOCK	I	Field discrimination signal from DVP "H"= ODD "L"= EVEN (with memory) VLOCK signal at clear scan (with no memory)
43	LATMEM	O	Serial control latch output of memory control IC PD3212A Latches at falling edge.
44	XPFR	O	PD0260A2 : 17MHz PLL control signal output H : Phase comparison L : Free-run PD0261A2 : Not used
45	XP/N2	O	PD0260A2 : NTSC/XPAL circuit switching signal output excepting VDEM H : NTSC L : PAL PD0261A2 : Not used
46	HQ	O	PD0260A2 : Control signal output of the High Quality circuit (analog NR) H : Through the HQ circuit L : Not through PD0261A2 : Not used
47	THLD	I	Track jump accelerating / decelerating signal input "L"= Others "H"= During accelerating / decelerating
48	LATDVP	O	PD6159B serial latch signal output Latches at falling edge.
49	SELTZC	O	TZC switch signal output "H"= at normal "L"= at CD/DVD disc discrimination
50	DOCINH	O	Control the clamp pulse and clamp killer circuit by tri-state value
51	XP/N1	O	PD0260A2 : NTSC/XPAL circuit switching signal output for VDEM H : NTSC L : PAL PD0261A2 : Not used
52	NROFF	O	Noise reduction control output by VDEM "L"= Normal "H"= Not NR
53	DSCDET	I	Disc present/absent detecting signal input by the tilt sum in the DVD P.U. mode "H"= Absent "L"= Present DEFECT input at LD P.U.
54	XTURNB	I	Turn switch input "H"= Side A / turn "L"= Side B
55	XTURNA	I	Turn switch input "H"= Side B / turn "L"= Side A
56	XLPO	I	LD P.U. out position detecting switch input "H"= LD P.U. active "L"= LD P.U. out position
57	VDET	I	Use for power abnormal signal input port "L"= Normal "H"= Abnormal
58	XFOK	I	Focus servo lock signal input "L"= Lock "H"= Unlock Use for lock detection of focus servo
59	WRQ	I	Subcode Q reading OK signal input "L"= NG "H"= OK This pin will be H when subcode Q data passed by CRC check.
60	AC3MUTE	O	Mute control signal output for AC3 Release MUTE during playback. "L"= Release MUTE "H"= MUTE
61	SQ1	O	Analog audio switching signal output 1/L "L"= Squelch OFF "H"= Squelch ON
62	SQ2	O	Analog audio switching signal output 2/R "L"= Squelch OFF "H"= Squelch ON
63	XCX	O	Analog audio CX noise reduction switching signal output "L"= CX ON "H"= CX OFF
64	XANA	O	Digital / Analog audio switching signal output "L"= Analog "H"= Digital

LA9700M (DVDM ASSY : IC101)

• **RF IC**

● **Block Diagram**



■ BA6195FP (DVDM ASSY : IC161)

• Spindle Driver

● Block Diagram



● Pin Function

No.	Pin Name	Function	No.	Pin Name	Function
1	OPOUT	OP amp. output pin	14	N.C.	Non Connection
2	N.C.	Non Connection	15	N.C.	
3	N.C.		16	N.C.	
4	BIAS	Bias pin	17	VCC	Power supply pin
5	DRIN'	Driver gain adjustment pin	18	N.C.	Non Connection
6	DRIN	Driver gain input pin	19	GND	Sub-strait GND pin
7	N.C.	Non Connection	20	GND	
8	N.C.		21	N.C.	Non Connection
9	N.C.		22	MUTE	Mute pin
10	N.C.		23	N.C.	Non Connection
11	N.C.		24	OPIN +	OP amp. non-inverting input pin
12	DROUT –	Driver negative output pin (for input)	25	OPIN –	OP amp. inverting input pin
13	DROUT +	Driver positive output pin (for input)			

LC78650E-P (DVDM ASSY : IC201)(DVL-909 only)

- **Servo DSP LSI**

Block Diagram



● Pin Function

No.	Pin Name	I/O	Function
1	PP5/SYNC	I/O	General-purpose port input/output / DVD sync. signal input
2	LEFM	O	Output the state that cut and out a signal which was binary-stated value EFM/EFM + with PCK.
3	EFMOUT	O	Output the state that was binary-stated value EFM/EFM + .
4	C2F	O	C2 flag output
5	ROMXA	O	ROMXA data output
6	ROMCK	O	Shift clock output for ROMXA data output
7	LRSY	O	L/R clock output for ROMXA data output
8	DVDD2	–	5V power supply
9	VSS	–	GND
10	XTALOUT	O	External system clock output
11	FSX	O	CD 1 frame sync. signal output
12	SBCK	I	Subcode reading out clock input
13	SFSY	O	Frame sync. signal output of subcode
14	PW	O	Subcode P, Q, R, S, T, U, V and W output
15	VSS	–	GND for oscillation circuit
16	XIN	I	Connect a crystal resonator (16.9344MHz)
17	XOUT	O	Connect a crystal resonator
18	DVDD1	–	3.3V power supply of the oscillation circuit
19	EMPH	O	Monitor the deemphasis
20	SBSY	O	Sync. signal output of the subcode block
21	DOUT	O	Output for the digital audio I/F
22	EFLG	O	Error correction state monitor of the error correction C1 and C2
23	FSEQ	O	Detection monitor of the CD/DVD frame sync. signal
24	FAST	O	Playback speed monitor
25	V_PB	O	Monitor output of the rough servo/CLV control
26	DRF	O	In focus monitor
27	TEST3	I	Test input 3
28	TES	I	Tracking error signal input
29	TEST2	I	Test input 2
30	JITT	I	Jitter quantity detecting signal input of EFM/EFM + PLL
31	TILTE	I	Tilt error signal input
32	RF_PH	I	RF peak hold signal input
33	RF_BH	I	RF bottom hold signal input
34	TE	I	Tracking error signal input
35	FE	I	Focus error signal input
36	SLCIST1	–	Current setting pin 1 of the constant current charge pump for SLC
37	SLCIST2	–	Current setting pin 2 of the constant current charge pump for SLC
38	SLCO1	–	Control output 1 for SLC
39	SLCO2	–	Control output 2 for SLC
40	TEST1	I	Test input 1
41	EFMIN	I	EFM/EFM + input
42	AVDD	–	5V power supply of A/D and D/A for servo
43	AVSS	–	GND of A/D and D/A for servo
44	AUXO	O	DA auxiliary output
45	TILTDO	O	Tilt control signal output
46	TBAL	O	Tracking balance control signal output
47	SLDO	O	Sled control signal output
48	SPDO	O	Spindle control signal output
49	FDO	O	Focus control signal output
50	TDO	O	Tracking control signal output

No.	Pin Name	I/O	Function
51	VREF	–	Reference level of A/D and D/A for servo
52	TEST4	I	Test input 4
53	HFL	O	Track detection signal output
54	LASER	O	For laser ON/OFF control
55	DVD_CDB	O	Disc discrimination result output
56	LCDCNTL	O	Pickup liquid shutter control signal output
57	PP6/FG	I/O	General-purpose port input/output / FG signal input
58	PP7/EVNT	I/O	General-purpose port input/output / Event counter input
59	RESB	I	Reset input
60	CSB	I	Chip select input
61	RDB	I	Internal state reading signal input
62	WRB	I	Command / data writing signal input
63	DVDD2	–	5V power supply
64	VSS	–	GND
65	P0	I/O	Command / data input/output
66	P1		
67	P2		
68	P3		
69	P4		
70	P5		
71	P6		
72	P7		
73	VSS	–	GND
74	DVDD1	–	3.3V power supply for internal logic
75	BUSYB	O	Busy signal output of command process
76	SQOUT	O	Serial output of subcode Q
77	CQCKB	I	Data read-out shift clock input of subcode Q
78	RWC	I	Serial output update permission input of subcode Q
79	WRQ	O	Read out ready monitor of subcode Q
80	VSS	–	PLL GND for internal system clock
81	VRPFR	–	VCO oscillation range setting of PLL for internal system clock
82	VCOC	–	Connect a PLL filter for internal system clock
83	VPDO		
84	DVDD2	–	PLL 5V power supply for internal system clock
85	PDO1	–	PLL filter connection pin 1 for EFM/EFM + playback
86	PDO2	–	PLL filter connection pin 2 for EFM/EFM + playback
87	PDO3	–	PLL filter connection pin 3 for EFM/EFM + playback
88	VSS	–	PLL GND for EFM/EFM + playback
89	PCKIST1	–	Current setting 1 of PLL constant current charge pump for EFM/EFM + playback
90	PCKIST2	–	Current setting 2 of PLL constant current charge pump for EFM/EFM + playback
91	DVDD2	–	PLL 5V power supply for EFM/EFM + playback
92	DVDFR	–	VCO oscillation range setting of PLL for EFM + playback
93	CDFR	–	VCO oscillation range setting of PLL for EFM playback
94	JV	O	Jitter monitor of PLL clock for EFM/EFM + playback
95	PCK	O	Bit clock output for EFM/EFM + playback
96	PP0	I/O	General-purpose port input/output
97	PP1		
98	PP2		
99	PP3		
100	PP4		

■ PD4889A (DVDM ASSY : IC501)

• Mechanism Control IC

● Pin Function

No.	Pin Name	I/O	Function	No.	Pin Name	I/O	Function
1	LODDRV	I/O	Loading motor drive output	33	XDSPRST	–	Reset pulse for servo DSP "L"
2	DVD/XCD	O	Clock switch H : DVD , L : CD	34	ASTB	O	Address strobe of multiplexed address/data bus "H"
3	AGOFF	O	Turn AGC of RF IC to OFF for "H"	35	XRST	I	CPU reset input "L"
4	EFLG	I	Count data input of error rate Measureable by using timer 1 and 2.	36	SBSY	INT	Subcode frame sync. input (H : S0+S1 period)
5	FSX	I	Error rate count area input (EFM frame sync.) H : C1 , L : C2	37	SHAKE	INT	Communication handshake of CLD mechanism controller "L" (DVL-909 only)
6	P35/PCL	–	Not used (pull down)	38	XABUSY	INT	DSP auto sequence busy input "L"
7	XTOFF	I/O	High impedance (input) at DEFECT ON "L" output at DEFECT OFF	39	XIRQ2	INT	LSI-11 interrupt input "L"
8	XCBUSY	I	DVD command reception is possible "L"	40	VDD	–	Power supply pin
9	VSS	–	GND	41	X2	–	Connect a ceramic resonator
10	MAD0	I/O	External address / data bus	42	X1	–	
11	MAD1			43	IC (Vpp)	–	GND
12	MAD2			44	XT2	–	Not used
13	MAD3			45	DVDPPK	I	Park position detection of compatible DVD pickup "L" (DVL-909 only)
14	MAD4			46	AVss	–	GND
15	MAD5			47	LODPOS	I	Loading and clamp position SW input
16	MAD6			48	SLDPOS	I	Slider position SW input
17	MAD7			49	DORPOS	I	Panel position SW input (DV-S9 only)
18	MA8	O	External address bus	50	XCURDET	I	Acutuator over-current detection input (former TRDLMT) "L" Servo OFF for 300 ms.
19	MA9			51	DR/XLD	O	Panel and loading switch of PWM output Panel : H , loading : L (DV-S9 only)
20	MA10			52	MON	O	Spindle motor ON output "H"
21	MA11			53	XCD2X	O	Not used
22	MA12			54	OEICG	O	"H" : OEIC gain up to 6dB
23	MA13			55	AVDD	–	Power supply pin
24	VSS	–	GND	56	AVREF	–	Reference power supply pin
25	MA14	O	External address bus	57	P_ERR	O	Not used
26	MA15			58	P21/SO1	–	Not used (pull down)
27	DRF	I	(FOK) Focus OK input	59	P22/XSK1	–	Not used (pull down)
28	V_PB	I	(LOCK) EFM servo lock signal "H"/"L"= rough servo / phase servo	60	XCSB	O	DSP parallel command setting output "L"
29	P62	–	Not used (pull down)	61	CLD	O	CLD circuit block switch (DVL-909 only)
30	WRQ	I	Readable flag of subcode Q	62	LDSO	I	Inputs serial communication output of CLD mechanism controller (DVL-909 only)
31	XRD	O	CPU read pulse "L"	63	LDSI	O	Outputs serial communication input of CLD mechanism controller (DVL-909 only)
32	XWR	O	CPU write pulse "L"	64	LDSCK	I	Inputs serial communication clock output of CLD mechanism controller (DVL-909 only)

SRM2B256SLMX70 (DVDM ASSY : IC502)

- **256 K SRAM (For Mechanism Control IC)**

● Block Diagram



● Pin Function

No.	Pin Name	Function	No.	Pin Name	Function
1	A14	Address input	15	I/O4	Data input/output
2	A12		16	I/O5	
3	A7		17	I/O6	
4	A6		18	I/O7	
5	A5		19	I/O8	
6	A4		20	$\overline{CS}$	Chip select
7	A3		21	A10	Address input
8	A2		22	$\overline{OE}$	Output enable
9	A1		23	A11	Address input
10	A0		24	A9	
11	I/O1	Data input/output	25	A8	
12	I/O2		26	A13	
13	I/O3		27	$\overline{WE}$	Write enable
14	VSS	GND (0V)	28	VDD	Power supply (2.7 to 5.5V)

VYW1536 (DVDM ASSY : IC603)(DV-505 and DVL-909 only)

- **Flash ROM**

● Block Diagram



● Pin Function

No.	Pin Name	Function	No.	Pin Name	Function
1	RY/$\overline{BY}$	Ready / Busy output	23	VCC	Power supply (+5.0V ± 10% or ± 5%)
2	A18	Address input	24	DQ4	Data input / output
3	A17		25	DQ12	
4	A7		26	DQ5	
5	A6		27	DQ13	
6	A5		28	DQ6	
7	A4		29	DQ14	
8	A3		30	DQ7	
9	A2		31	DQ15/A-1	Data input/output / address input
10	A1		32	VSS	Ground
11	A0		33	$\overline{BYTE}$	Switch the 8 bit and 16 bit modes
12	$\overline{CE}$	Chip enable	34	A16	Address input
13	VSS	Ground	35	A15	
14	$\overline{OE}$	Output enable	36	A14	
15	DQ0	Data input/output	37	A13	
16	DQ8		38	A12	
17	DQ1		39	A11	
18	DQ9		40	A10	
19	DQ2		41	A9	
20	DQ10		42	A8	
21	DQ3		43	$\overline{WE}$	Write enable
22	DQ11		44	$\overline{RESET}$	Hardware reset

PD3381A (DVDM ASSY : IC601)

- **System Control CPU**

● **Block Diagram**



● Pin Function

No.	Pin Name	I/O	Function
1	PB14/TP14/$\overline{\text{IRQ6}}$	I/O	16 bit input/output (port B) / Timing pattern output / Interruption request
2	PB15/TP15/$\overline{\text{IRQ7}}$		
3	VSS	I	Ground
4	AD0	I/O	16 bit bilateral data bus
5	AD1		
6	AD2		
7	AD3		
8	AD4		
9	AD5		
10	AD6		
11	AD7		
12	VSS	I	Ground
13	AD8	I/O	16 bit bilateral data bus
14	AD9		
15	VCC	I	Power supply
16	AD10	I/O	16 bit bilateral data bus
17	AD11		
18	AD12		
19	AD13		
20	AD14		
21	AD15		
22	VSS	I	Ground
23	A0 ($\overline{\text{HBS}}$)	O	Address bus output (upper byte strobe signal)
24	A1	O	Address bus output
25	A2		
26	A3		
27	A4		
28	A5		
29	A6		
30	A7		
31	VSS	I	Ground
32	A8	O	Address bus output
33	A9		
34	A10		
35	A11		
36	A12		
37	A13		
38	A14		
39	A15		
40	VSS	I	Ground
41	A16	O	Address bus output
42	A17		
43	VCC	I	Power supply

No.	Pin Name	I/O	Function
44	A18	O	Address bus output
45	A19		
46	A20		
47	A21		
48	$\overline{CS0}$	O	Chip select signal
49	$\overline{CS1}$/$\overline{CASH}$	O	Chip select signal / Column address strobe timing signal on the upper side of DRAM
50	$\overline{CS2}$	O	Chip select signal
51	$\overline{CS3}$/$\overline{CASL}$	O	Chip select signal / Column address strobe timing signal on the lower side of DRAM
52	VSS	I	Ground
53	PA0/$\overline{CS4}$/TIOCA0	I/O	16 bit input/output (port A) / Chip select signal / ITU input capture input/ITU output compare output (channel 0)
54	PA1/$\overline{CS5}$/$\overline{RAS}$	I/O	16 bit input/output (port A) / Chip select signal / Low address strobe timing signal of DRAM
55	PA2/$\overline{CS6}$/TIOCB0	I/O	16 bit input/output (port A) / Chip select signal / ITU input capture input/ITU output compare output (channel 0)
56	PA3/$\overline{CS7}$/$\overline{WAIT}$	I/O	16 bit input/output (port A) / Chip select signal / Wait input for bus cycle
57	PA4/$\overline{WRL}$ ($\overline{WR}$)	I/O	16 bit input/output (port A) / External lower 8 bit writing (output at writing)
58	PA5/$\overline{WRH}$ ($\overline{LBS}$)	I/O	16 bit input/output (port A) / External upperr 8 bit writing (lower byte strobe signal)
59	PA6/$\overline{RD}$	I/O	16 bit input/output (port A) / External reading out
60	PA7/$\overline{BACK}$	I/O	16 bit input/output (port A) / Bus claim request acknowledge
61	VSS	I	Ground
62	PA8/$\overline{BREQ}$	I/O	16 bit input/output (port A) / Bus claim request
63	PA9/$\overline{AH}$/$\overline{IRQOUT}$/$\overline{ADTRG}$	I/O	16 bit input/output (port A) / Address hold timing signal / Interruption request output at slave / A/D conversion trigger input
64	PA10/DPL/TIOCA1	I/O	16 bit input/output (port A) / Data bus parity on the lower side / ITU input capture input/ITU output compare output (channel 1)
65	PA11/DPH/TIOCB1	I/O	16 bit input/output (port A) / Data bus parity on the upper side / ITU input capture input/ITU output compare output (channel 1)
66	PA12/$\overline{IRQ0}$/DACK0/TCLKA	I/O	16 bit input/output (port A) / Interruption request / DMA transfer request reception (channel 0) / ITU timer clock input
67	PA13/$\overline{IRQ1}$/$\overline{DREQ0}$/TCLKB	I/O	16 bit input/output (port A) / Interruption request / DMA transfer request (channel 0) / ITU timer clock input
68	PA14/$\overline{IRQ2}$/DACK1	I/O	16 bit input/output (port A) / Interruption request / DMA transfer request reception (channel 1)
69	PA15/$\overline{IRQ3}$/$\overline{DREQ1}$	I/O	16 bit input/output (port A) / Interruption request / DMA transfer request (channel 1)
70	VCC	I	Power supply
71	CK	O	System clock output
72	VSS	I	Ground
73	EXTAL	I	Crystal oscillator input External clock input
74	XTAL	I	Crystal oscillator input
75	VCC	I	Power supply
76	NMI	I	Non-maskable interruption input
77	VPP	I	Power supply of PROM program
78	$\overline{WDTOVF}$	O	Watchdog timer over-flow output
79	$\overline{RES}$	I	Reset input
80	MD0	I	Mode setting pins
81	MD1		
82	MD2		
83	VCC	I	Power supply
84	VCC		

No.	Pin Name	I/O	Function
85	AVCC	I	Analog power supply
86	AVREF	I	Analog reference power supply
87	PC0/AN0	I	8 bit input (port C) / Analog signal input
88	PC1/AN1		
89	PC2/AN2		
90	PC3/AN3		
91	AVSS	I	Analog Ground
92	PC4/AN4	I	8 bit input (port C) / Analog signal input
93	PC5/AN5		
94	PC6/AN6		
95	PC7/AN7		
96	VSS	I	Ground
97	PB0/TP0/TIOCA2	I/O	16 bit input/output (port B) / Timing pattern output / ITU input capture input/ITU output compare output (channel 2)
98	PB1/TP1/TIOCB2		
99	VCC	I	Power supply
100	PB2/TP2/TIOCA3	I/O	16 bit input/output (port B) / Timing pattern output / ITU input capture input/ITU output compare output (channel 3)
101	PB3/TP3/TIOCB3		
102	PB4/TP4/TIOCA4	I/O	16 bit input/output (port B) / Timing pattern output / ITU input capture input/ITU output compare output (channel 4)
103	PB5/TP5/TIOCB4		
104	PB6/TP6/TOCXA4/TCLKC	I/O	16 bit input/output (port B) / Timing pattern output / ITU output compare output (channel 4) / ITU timer clock input
105	PB7/TP7/TOCXB4/TCLKD		
106	VSS	I	Ground
107	PB8/TP8/RXD0	I/O	16 bit input/output (port B) / Timing pattern output / Receive data input (channel 0)
108	PB9/TP9/TXD0	I/O	16 bit input/output (port B) / Timing pattern output / Transmission data output (channel 0)
109	PB10/TP10/RXD1	I/O	16 bit input/output (port B) / Timing pattern output / Receive data input (channel 1)
110	PB11/TP11/TXD1	I/O	16 bit input/output (port B) / Timing pattern output / Transmission data output (channel 1)
111	PB12/TP12/$\overline{\text{IRQ4}}$/SCK0	I/O	16 bit input/output (port B) / Timing pattern output / Interruption request / Serial clock input/output (channel 0)
112	PB13/TP13/$\overline{\text{IRQ5}}$/SCK1	I/O	16 bit input/output (port B) / Timing pattern output / Interruption request / Serial clock input/output (channel 1)

■ MB86371 (DVDM ASSY : IC801)

• MPEG2 Decoder LSI For DVD

● Block Diagram



● Pin Function

No.	Pin Name	I/O	Function	No.	Pin Name	I/O	Function
1	CLKSEL	I	ON/OFF signal of PLL ("H" : ON, "L" : OFF)	27	VDD	–	3.3V power supply
2	DIGCPN7	O	Digital component signal output (MSB) Digital Y signal output (9-bit) (MSB)	28	DIGCOMP4	O	Digital composite signal output Digital C signal output
3	VSS	–	GND	29	DIGCOMP3		
4	DIGCPN6	O	Digital component signal output Digital Y signal output (9-bit)	30	DIGCOMP2		
5	DIGCPN5			31	DIGCOMP1		
6	DIGCPN4			32	DIGCOMP0		Digital composite signal output (LSB) Digital C signal output (LSB)
7	DIGCPN3			33	DACK	O	27 MHz clock output
8	DIGCPN2			34	N.C.	–	Non connection
9	DIGCPN1			35	VSSA3	–	GND (D/A converter)
10	VDD	–	3.3V power supply	36	ANAC	O	Analog color (C) output signal
11	DIGCPN0	O	Digital component signal output (LSB) Digital Y signal output (9-bit) (LSB)	37	VDDA3	–	3.3V power supply (for built-in D/A converter only)
12	RBSEL	O	Cb and Cr discrimination signal at the digital component signal output. LSB at the digital Y signal output.	38	VSSA2	–	GND (D/A converter)
13	XHS	O	Horizontal sync. output signal	39	ANAY	O	Analog luminance (Y) output signal
14	XVS	O	Vertical sync. output signal	40	VDDA2	–	3.3V power supply (for built-in D/A converter only)
15	VSS	–	GND	41	VREF	I	Reference voltage for D/A converter
16	XRESET	I	LSI reset signal	42	VRO	O	Internal current setting pin of D/A converter
17	XLDCSYNC	I	External sync. signal input (LD mode)	43	N.C.	–	Non connection
18	KEY	O	KEY signal for LD and OSD overlay (LD mode)	44	VSSA1	–	GND (D/A converter)
19	PD	O	Phase comparison result output signal of horizontal sync. (LD mode)	45	ANACOMP	O	Analog composite output signal
20	VFLD	O	Field discrimination signal at the digital signal output H : even field L : odd field	46	VDDA1	–	3.3V power supply (for built-in D/A converter only)
21	DIGCOMP9	O	Digital composite signal output (MSB) Digital C signal output (MSB)	47	BF	O	Burst flag signal
22	DIGCOMP8		Digital composite signal output Digital C signal output	48	XBLK	O	H/V composite blanking signal
23	DIGCOMP7			49	N.C.	–	Non connection
24	DIGCOMP6			50	VSS	–	GND
25	DIGCOMP5			51	TEST0	–	Normally, set to "open".
26	VSS	–	GND	52	TEST1	–	"L" status normally

No.	Pin Name	I/O	Function	No.	Pin Name	I/O	Function
53	DAIIN	I	Digital data input of external input (SPDIF)	92	HADRS10	I	CPU address bus signal (MSB)
54	CDDATA	I	Audio data input of external input (correspond to CD)	93	HADRS9	I	CPU address bus signal
55	CDLR	I	Data channel clock input of external input (correspond to CD)	94	HADRS8		
56	CDBCK	I	Data clock input of external input (correspond to CD)	95	HADRS7		
57	AODATA3	O	Audio decode data	96	VSS	–	GND
58	AODATA2			97	VDD	–	3.3V power supply
59	AODATA1			98	HADRS6	I	CPU address bus signal
60	VSS	–	GND	99	HADRS5		
61	VDD	–	3.3V power supply	100	HADRS4		
62	AODATA0	O	Audio decode data	101	HADRS3		
63	AOPCM	O	Digital audio interface output (compression data)	102	HADRS2		CPU address bus signal (LSB)
64	AODAI	O	Digital audio interface output (decode data)	103	HDATA15	I/O	CPU data bus signal (MSB)
65	LRCK	O	Data channel clock for D/A and digital filter	104	HDATA14		CPU data bus signal
66	AOMCK	O	Master clock for D/A and digital filter	105	HDATA13		
67	BCK	O	Bit clock for D/A and digital filter	106	HDATA12		
68	ICED1	–	Pin for emulator Normally, set to "open".	107	VSS	–	GND
69	ICED0			108	HDATA11	I/O	CPU data bus signal
70	ICEBRK			109	HDATA10		
71	XDSPRST			110	HDATA9		
72	VSS	–	GND	111	HDATA8		
73	N.C.	–	Non connection	112	HDATA7		
74	TEST2	–	Normally, set to "open".	113	HDATA6		
75	TEST3			114	VDD	–	3.3V power supply
76	TEST4			115	HDATA5	I/O	CPU data bus signal
77	TEST5			116	HDATA4		
78	SD7	I	Parallel data input	117	HDATA3		
79	VDD	–	3.3V power supply	118	HDATA2		
80	SD6	I	Parallel data input	119	VSS	–	GND
81	SD5			120	HDATA1	I/O	CPU data bus signal
82	SD4			121	HDATA0		CPU data bus signal (LSB)
83	SD3			122	BUSSEL	I	Bus width selection signal (0 : 8-bit bus, 1 : 16-bit bus)
84	SD2			123	XOSDACK	I	OSD data acknowledge signal
85	VSS	–	GND	124	XOSDREQ	O	OSD data request signal
86	SD1	I	Parallel data input	125	HCPUSEL1	I	CPU selection signal (00 :SPARC, 01 :86 system, 10 :68 system, 11 :Reserve)
87	SD0			126	HCPUSEL0		
88	XERR	I	Error input signal	127	XINT3	O	Interrupt request signal to the CPU
89	XSACK	I	Acknowledge signal	128	XINT2		
90	XTEST	I	Set to "H" at normal use	129	XINT1		
91	SREQ	O	Data request signal	130	VSS	–	GND

No.	Pin Name	I/O	Function	No.	Pin Name	I/O	Function
131	VDD	–	3.3V power supply	170	XMDRCAS	O	CAS signal for SDRAM
132	XINT0	O	Interrupt request signal to CPU	171	XMDRDQM1	O	Input mask / output enable signal for SDRAM
133	XEXTRDY	O	SPARC, 68 system : Ready signal to CPU 86 system : Acknowledge (ACK) signal to CPU	172	VSS	–	GND
134	HRW	I	CPU read / write signal	173	XMDRWE	O	Write enable signal for SDRAM
135	HCLKIN	I	Host clock input	174	XMDRDQM0	O	Input mask / output enable signal for SDRAM
136	XHCS	I	LSI chip select signal	175	MDRDAT8	I/O	Data bus signal for SDRAM
137	XHAS	I	SPARC, 68 system : CPU address strobe 86 system : CPU address status	176	VSS	–	GND
138	XHBE3	I	CPU byte enable signal	177	MDRDAT7	I/O	Data bus signal for SDRAM
139	XHBE2			178	MDRDAT9		
140	XHBE1			179	MDRDAT6		
141	XHBE0			180	MDRDAT10		
142	VSS	–	GND	181	MDRDAT5		
143	MDRADR4	O	Address signal for SDRAM	182	VSS	–	GND
144	MDRADR3			183	VDD	–	3.3V power supply
145	MDRADR5			184	MDRDAT11	I/O	Data bus signal for SDRAM
146	MDRADR2			185	MDRDAT4		
147	VDD	–	3.3V power supply	186	MDRDAT12		
148	VSS	–	GND	187	MDRDAT3		
149	MDRADR6	O	Address signal for SDRAM	188	MDRDAT13		
150	MDRADR1			189	VSS	–	GND
151	MDRADR7			190	MDRDAT2	I/O	Data bus signal for SDRAM
152	MDRADR0		Address signal for SDRAM (LSB)	191	MDRDAT14		
153	MDRADR8		Address signal for SDRAM	192	MDRDAT1		
154	VSS	–	GND	193	MDRDAT15		Data bus signal for SDRAM (MSB)
155	TEST6	–	"L" status normally	194	MDRDAT0	I/O	Data bus signal for SDRAM (LSB)
156	TEST7			195	VSS	–	GND
157	TEST8			196	N.C.	–	Non connection
158	TEST9			197	ICK27M	I	System clock input
159	MDRADR10	O	Address signal for SDRAM	198	VSS	–	GND
160	MDRADR9			199	OCK27M	O	System clock output
161	MDRADR11		Address signal for SDRAM (MSB)	200	VSSA(VCO)	–	GND (for VCO only)
162	XMDRCS	O	Chip select signal for SDRAM	201	VDDA(VCO)	–	3.3V power supply (for VCO only)
163	MDRCKE	O	Clock enable signal for SDRAM	202	ILPF	O	PLL block inverter output for audio
164	VSS	–	GND	203	MLPF	I	PLL block inverter input for audio
165	VDD	–	3.3V power supply	204	OLPF	O	Phase detector output for audio
166	XMDRRAS	O	RAS signal for SDRAM	205	OVCO	I	VCO input for audio clock
167	MDRCLK	O	Clock output signal for SDRAM	206	VSS	–	GND
168	VSS	–	GND	207	XPLLRST	I	PLL section reset signal
169	MDRCLKIN	I	Clock input signal for SDRAM	208	XSYNCRST	I	SYNC reset signal

MB811171622A-100FN (DVDM ASSY : IC802)

• Code Buffer (16M bit SDRAM)

● Block Diagram



● Pin Function

No.	Pin Name	Function	No.	Pin Name	Function
1	VCC	Power supply (+ 3.3V)	26	VSS	Ground
2	DQ0	Data input/output	27	A4	Address input Row : A0 to A10 , Column : A0 to A7
3	DQ1		28	A5	
4	VSSQ	Ground	29	A6	
5	DQ2	Data input/output	30	A7	
6	DQ3		31	A8	
7	VCCQ	Power supply (+ 3.3V)	32	A9	
8	DQ4	Data input/output	33	DU	Don't use (use for open)
9	DQ5		34	CKE	Clock enable
10	VSSQ	Ground	35	CLK	Clock input
11	DQ6	Data input/output	36	DQMU	Input mask / Output enable
12	DQ7		37	DU	Don't use (use for open)
13	VCCQ	Power supply (+ 3.3V)	38	VCCQ	Power supply (+ 3.3V)
14	DQML	Input mask / Output enable	39	DQ8	Data input/output
15	WE	Write enable	40	DQ9	
16	CAS	Column address strobe	41	VSSQ	Ground
17	RAS	Row address strobe	42	DQ10	Data input/output
18	CS	Chip select	43	DQ11	
19	A11 (BA)	Bank select	44	VCCQ	Power supply (+ 3.3V)
20	A10/AP	Address input Row : A0 to A10 , Column : A0 to A7 / Auto pre-charge enable	45	DQ12	Data input/output
21	A0	Address input Row : A0 to A10 , Column : A0 to A7	46	DQ13	
22	A1		47	VSSQ	Ground
23	A2		48	DQ14	Data input/output
24	A3		49	DQ15	
25	VCC	Power supply (+ 3.3V)	50	VSS	Ground

■ CY2081SL-611 (DVDM ASSY : IC813)

• **Clock Generate IC**

● **Block Diagram**



● **Pin Function**

No.	Pin Name	Function
1	CLKA	Configurable clock output
2	GND	Ground
3	XTALIN	Reference crystal input or external reference clock input
4	XTALOUT	Reference crystal feedback
5	CLKB	Configurable clock output
6	CLKC	Configurable clock output
7	VDD	Voltage supply
8	OE/PD/FS/SUSPEND	Output control pin Either active-High output enable, active-Low power down, CLKA frequency select, or active-Low suspend input

■ PD2058A (DVDM ASSY : IC901)(DV-505 and DVL-909 only)

• Digital Signal Processor For Audio

● Block Diagram



● Pin Function

No.	Pin Name	I/O	Function
1	TP8	O	Test data output pin Normally, use with open.
2	TP7		
3	TP6		
4	VDD	–	Power supply pin
5	VSS	–	Ground pin
6	TP5	O	Test data output pin Normally, use with open.
7	TP4		
8	TP3		
9	TP2		
10	TP1		
11	TP0		

No.	Pin Name	I/O	Function	
12	VSSR	–	Ground pin for internal delay RAM (DLRAM)	
13	VDDR	–	Power supply pin for internal delay RAM (DLRAM)	
14	VSS	–	Ground pin	
15	SDO2	O	Serial data output pin Output data length is able to select the 24-bit or 16-bit by controlling the microprocessor.	
16	SDO1			
17	SDO0			
18	SDI1	I	Serial data input pin Input data length is able to select the 24-bit or 16-bit by controlling the microprocessor.	
19	SDI0			
20	LR	O	LR clock output pin (1 fs)	
21	WCK	O	Word clock output pin (2 fs)	
22	FS32	O	Bit clock output pin (32 fs)	
23	FS64	O	Bit clock output pin (64 fs)	
24	EBC0	I	Bit clock input pin Inputs shift clock for SDO0/1/2 data output.	
25	EBCI1	I	Bit clock input pin Inputs shift clock for SDI0/1 data input.	For SDI1 data input
26	EBCI0			For SDI0 data input
27	ELRO	I	LR clock input pin Inputs LR clock for SDO0/1/2 data output.	
28	ELRI1	I	LR clock input pin Inputs LR clock for SDI0/1 data input.	For SDI1 data input
29	ELRI0			For SDI0 data input
30	SYNC	I	Sync. signal input pin Turn the program counter into "0" forcibly by the edge of SYNC signal. Moreover, set the polarity by controlling the microprocessor.	
31	VDD	–	Power supply pin	
32	XI	I	Crystal oscillator connection pin / external clock input pin	
33	XO	O	Crystal oscillator connection pin	
34	VSS	–	Ground pin	
35	CKSL	I	Oscillation clock switch pin L : correspond to 384 fs H : correspond to 512 fs	
36	PLOFF	I	X'tal oscillation mode / VCO oscillation mode switch pin L :built-in VCO oscillation mode H :X'tal oscillation mode	
37	PD	O	Phase comparison data output pin	
38	VSSA	–	Analog ground pin	
39	AMPO	O	Amp. output pin for low-pass filter	
40	AMPI	I	Amp. input pin for low-pass filter	
41	VDDA	–	Analog power supply pin	
42	TES0	I	Test pin Normally, use for "H" or open.	
43	TES1			
44	TES2			
45	$\overline{\text{RST}}$	I	Reset signal input pin	
46	$\overline{\text{CS}}$	I	Chip select signal input pin When $\overline{\text{CS}}$ is L active, data is able to transfer from the microprocessor.	
47	IFCD	I	Command or data input mode selection pin from the microprocessor Recognize the command for "H" period and the data for "L" period.	
48	IFDI	I	Microprocessor data input pin Receive the command and data by LSB first.	
49	IFDO	O	Data output pin of data bus (DBUS) Transmit the data of data bus to the microprocessor by LSB first.	
50	IFCK	I	Shift clock input pin for microprocessor data	
51	$\overline{\text{ACK}}$	O	Acknowledge signal output pin for microprocessor When parity of command and data is OK, outputs the acknowledge signal.	
52	VSS	–	Ground pin	
53	TP16	O	Test data output pin Normally, use with open.	
54	TP15			
55	TP14			
56	TP13			
57	TP12			
58	TP11			
59	TP10			
60	TP9			

5. FL INFORMATION

■ VAW1046 (FLKB ASSY : V101)(DV-505 and DVL-909 only)

• FL DISPLAY



• ANODE AND GRID ASSIGNMENT

	G1	G2	G3	G4	G5	G6	G7	G8	G9	G10	G11
P1	P1	P1	P1	P1	P1	P1	P1	P1	P1	P1	P1
P2	ANGLE	P2	P2	P2	P2	P2	P2	P2	P2	P2	P2
P3	TITLE	P3	P3	P3	P3	P3	P3	P3	P3	P3	P3
P4	LAST MEMO	P4	P4	P4	P4	P4	P4	P4	P4	P4	P4
P5	CONDITION	P5	P5	P5	P5	P5	P5	P5	P5	P5	P5
P6	P6	P6	P6	P6	P6	P6	P6	P6	P6	P6	P6
P7	CHP/TRK	P7	P7	P7	P7	P7	P7	P7	P7	P7	P7
P8	P8	P8	P8	P8	P8	P8	P8	P8	P8	P8	P8
P9	REMAIN	P9	P9	P9	P9	P9	P9	P9	P9	P9	P9
P10	DOLBY DIGITAL	P10	P10	P10	P10	P10	P10	P10	P10	P10	P10
P11	GUI	P11	P11	P11	P11	P11	P11	P11	P11	P11	P11
P12	96kHz	P12	P12	P12	P12	P12	P12	P12	P12	P12	P12
P13		P13	P13	P13	P13	P13	P13	P13	P13	P13	P13
P14		P14	P14	P14	P14	P14	P14	P14	P14	P14	P14
P15	TOTAL			▷			▷			○ ○	

• PIN ASSIGNMENT

Pin No.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17
Assignment	F1	F1	NP	P15	P14	P13	P12	P11	P10	P9	P8	P7	P6	P5	P4	P3	P2

Pin No.	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34
Assignment	P1	G11	G10	G9	G8	NL	NL	G7	G6	G5	G4	G3	G2	G1	NP	F2	F2

F1, F2 : Filament G1~G11 : Grid P1~P15 : Anode NP : No Pin NL : No Lead